



<http://www.ebiz-tcf.eu>

DRAFT

IMPLEMENTATION GUIDE

TRANSACTION "TEXTILE PRINTING COMMISSION ORDER"

Version: draft

Date of release: 17/5/2019

Document code: G024

technical Documentation: <http://www.ebiz.enea.it>

XML Schemas repository: <http://www.ebiz.enea.it/moda-ml/repository/schema/draft/default.asp>

Guides repository: <http://www.ebiz.enea.it/moda-ml/repository/guide/draft/default.asp>

Guide filename: G024-eBIZ-TextilePrintingCommissionOrder.pdf

0. PREMISE

This document contains a proposal for the updating and extension of eBIZ specifications starting from the eBIZ version released as CEN CWA 16667 in 2013. Under the name of 'Draft version' it is reported the result of an extensive work of analysis and consultation aimed at developing and maintaining eBIZ specifications.

In particular, the content of this proposal is the result of various activities, mainly those carried out within the framework of the **eBIZ 4.0 project** funded by the European Commission, call COS-DESIGN-2015-3-06, topic COS-2015-DESIGN-2.

The technical contents are backwards compatible with the latest official published version.

1. BUSINESS DESCRIPTION

1.1 Scope

The present guide has been issued to assist the companies of the Textile-Clothing sector in the implementation of the standard XML document type "TEXTILE PRINTING COMMISSION ORDER", providing all the instruction required for its use in the context of e-commerce between Textile Subcontractors and their Customers shown in the enclosed diagram.

All the rules required for the construction and validation of the document are embedded into the specific XML-Schema, which is detailed in section "Implementation guide".

1.2 Generalities

The Printing commission order is used by a Fabric Producer to commit to a Subcontractor the printing of fabric.

When the Issuer of the Commission requires different manufacturing operations in sequence to different Subcontractors, he can use this document not only as work order but also as a despatch order to send the semi-finished product to a successive Subcontractor


As a general rule, the Printing commission order specifies only the manufacturing technology (if required) and the characteristics of the end product of each operation and specifies the components used to manufacture that product

It must be noted that this end product can be, in turn, a component for a successive manufacturing operation

The definition of any "manufacturing parameters" is left to the Subcontractor; sometimes however these parameters can be specified by the Issuer of the Commission itself, that can define machines and machine parameters in the Commission Order

1.3. Possible scenario

Subcontracted fabric printing



1.4. Best practices

Textile Dyeing-Finishing Order can be used instead of Textile Printing Order when printing is associated to dyeing-finishing operations and these are prevalent.

2. IMPLEMENTATION GUIDE

2.1 General structure of XML document

All the business data that can be exchanged through this class of documents are shown in the following "document structure", that provides a simplified vision of the Schema.

In particular:

- the two numbers following each element define its "cardinality" (minimum and maximum number of occurrences); the minimum equal zero indicates that the element is optional, the minimum greater than zero indicates that is mandatory;
- the bold character denotes the complex elements (aggregates of simple elements) that were built for the sake of functionality and re-usability of some complex informations sets. The child elements in each parent element are easily spotted as "indented";
- the symbol "@" denotes an attribute of the preceding element; here "the usage indicator (optional, required, ...)" is shown in square brackets.

Structure

TEXPrintOrder

@msgfunction [Optional] [Default= OR]

@version [Optional] [Default= draft]

@useProfile [Optional]

| **TPCOheader 1-1**

| | msgN 1-1

| | - choose -

| | msgID 0-1

| | - or -

| | docID 0-1

| | *@numberingOrg [Optional]*

| | - end choose -

| | msgDate 1-1

| | *@dateForm [Optional]*

| | season 0-1

| | *@numberingOrg [Optional]*

| | *@codeList [Optional]*

| | *@listName [Optional]*

| | *@listVersion [Optional]*

| | msgCurrency 0-1

| | **refDoc 0-9**

| | *@docType [Required]*

| | | docID 1-2

| | | *@numberingOrg [Optional]*

| | | docDate 0-1

| | | *@dateForm [Optional]*

| | | season 0-1

| | | *@numberingOrg [Optional]*

| | | *@codeList [Optional]*

| | | *@listName [Optional]*

| | | *@listVersion [Optional]*

| | | itemID 0-1

| | | **attachment 0-1**

| | | *@uid [Optional]*

| | | | fileName 0-1

| | | | *@numberingOrg [Optional]*

| | | | binaryObject 0-1

| | | | *@format [Optional]*

| | | | *@mime [Optional]*

| | | | *@encoding [Optional]*

| | | | *@characterSet [Optional]*

```

| | | | externalReference 0-99
| | | | | uri 1-1
| | | | | @isURL [Optional] [Default= true]
| | | | | mimeTypeCode 0-1
| | | | | formatCode 0-1
| | | | | encodingCode 0-1
| | | | | characterSetCode 0-1
| | | | buyer 1-1
| | | | | @logo [Optional]
| | | | | @sender [Optional]
| | | | | | id 1-1
| | | | | | | @numberingOrg [Optional]
| | | | | | additionalIdentifier 0-9
| | | | | | | @numberingOrg [Optional]
| | | | | | | @idQualifier [Optional]
| | | | | | legalName 0-1
| | | | | | dept 0-1
| | | | | | subDept 0-1
| | | | | | person 0-1
| | | | | | | @email [Optional]
| | | | | | | @phone [Optional]
| | | | | | | @fax [Optional]
| | | | | | street 0-1
| | | | | | city 0-1
| | | | | | subCountry 0-1
| | | | | | country 0-1
| | | | | | postCode 0-1
| | | | | subContractor 1-1
| | | | | | @sender [Optional]
| | | | | | | id 1-1
| | | | | | | | @numberingOrg [Optional]
| | | | | | | legalName 0-1
| | | | | | | dept 0-1
| | | | | | | subDept 0-1
| | | | | | | person 0-1
| | | | | | | | @email [Optional]
| | | | | | | | @phone [Optional]
| | | | | | | | @fax [Optional]
| | | | | | | street 0-1
| | | | | | | city 0-1
| | | | | | | subCountry 0-1
| | | | | | | country 0-1
| | | | | | | postCode 0-1
| | | | | thirdParty 0-5
| | | | | | @VAT [Optional]
| | | | | | @role [Required]
| | | | | | @sender [Optional]
| | | | | | | id 1-1
| | | | | | | | @numberingOrg [Optional]
| | | | | | | legalName 0-1
| | | | | | | dept 0-1
| | | | | | | subDept 0-1
| | | | | | | person 0-1
| | | | | | | | @email [Optional]
| | | | | | | | @phone [Optional]
| | | | | | | | @fax [Optional]
| | | | | | | street 0-1
| | | | | | | city 0-1
| | | | | | | subCountry 0-1
| | | | | | | country 0-1
| | | | | | | postCode 0-1

```

| | note 0-99
| | @numberingOrg [Optional]
| | @codeList [Optional]
| | @noteLabel [Optional]

| **terms 0-1**

| | **payment 0-5**
| | @finDiscount [Optional]
| | @finSurcharge [Optional]
| | - choose -

| | | payTerm 1-1
| | - or -

| | | payTermText 1-1
| | - end choose -

| | | payMode 0-1

| | **insPayment 0-5**

| | @part [Required]

| | - choose -

| | | payTerm 1-1

| | - or -

| | | payTermText 1-1

| | - end choose -

| | | payMode 0-1

| | **trade 0-1**

| | - choose -

| | | incoTermText 1-1

| | - or -

| | | incoTerm 1-1

| | - end choose -

| | | location 0-1

| | | @LRI [Optional]

| | **transInfo 0-5**

| | @transReason [Optional]

| | @progr [Optional]

| | | transMode 1-1

| | | carrier 0-1

| | | deliveryPlace 0-1

| | | grossWeight 0-1

| | | @um [Required]

| | | netWeight 0-1

| | | @um [Required]

| | | transMeans 0-1

| | | transCondition 0-3

| | | transConditionText 0-1

| | | despatchPlace 0-1

| | | despatchDate 0-1

| | | @dateForm [Optional]

| | | delEffectiveDate 0-1

| | | @dateForm [Optional]

| | **allowanceCharge 0-9**

| | @um [Optional]

| | @VAT [Optional]

| | @minQty [Optional]

| | @currency [Optional]

| | @maxQty [Optional]

| | - choose -

| | | AC_category 1-1

| | - or -

| | | AC_categoryText 1-1

| | - end choose -

| | - choose -

```

| | | AC_percent 1-1
| | | - or -
| | | AC_amount 1-1
| | | - end choose -
| | | dtScheme 0-1
| | |   @taxType [Required]
| | |   taxCategory 0-1
| | |   taxRate 0-1
| | |   legalRef 0-1
| | |   @codeList [Required]
| | |   note 0-99
| | |   @numberingOrg [Optional]
| | |   @codeList [Optional]
| | |   @noteLabel [Optional]

```

TPCObody 1-1

```

| | TPCOitem 1-unbounded
| |   @productLevel [Optional] [Default= END]
| |   lineN 1-1
| |   @VAT [Optional]
| |   fabricProd 1-1
| |     @CTest [Optional]
| |     texCode 1-1
| |       @numberingOrg [Optional]
| |       art 1-1
| |       @numberingOrg [Optional]
| |       @codeList [Optional]
| |       @listName [Optional]
| |       @listVersion [Optional]
| |       pattern 0-1
| |       @numberingOrg [Optional]
| |       @codeList [Optional]
| |       @listName [Optional]
| |       @listVersion [Optional]
| |       color 0-1
| |       @numberingOrg [Optional]
| |       @codeList [Optional]
| |       @listName [Optional]
| |       @listVersion [Optional]
| |       added 0-9
| |       @numberingOrg [Optional]
| |       @addType [Optional]
| |       description 0-unbounded
| |       @ln [Optional]
| |     fabricCompos 0-1
| |       percCompos 1-9
| |       @fibre [Required]
| |     fabricWidth 0-1
| |     @um [Optional] [Default= CMT]
| |     fabricSpecs 0-99
| |     - choose -
| |     | fabricCharText 1-1
| |     - or -
| |     | fabricChar 1-1
| |     - end choose -
| |     specValue 0-1
| |     @um [Optional]
| |     @source [Optional]
| |     @method [Optional]
| |     @application [Optional]
| |     @CV [Optional]

```

```

- choose -
| | | | tolerance 0-2
| | | | @um [Required]
- or -
| | | | pcTolerance 0-2
| | | | @um [Optional]
- end choose -
- choose -
| | | | pieceChain 0-99
| | | | serialN 1-9
| | | | @numberingOrg [Optional]
| | | | @idQualifier [Optional]
| | | | pieceLength 0-1
| | | | @um [Optional] [Default= MTR]
| | | | pieceWidth 0-1
| | | | @um [Optional] [Default= CMT]
| | | | pieceWeight 0-1
| | | | @um [Optional] [Default= KGM]
| | | | lotN 0-1
| | | | @numberingOrg [Optional]
| | | | dyeN 0-1
| | | | @numberingOrg [Optional]
| | | | packageN 0-1
| | | | @numberingOrg [Optional]
| | | | @packageContainerN [Optional]
| | | | piecePack 0-1
- choose -
| | | | piecePackText 1-1
- or -
| | | | pieceInnWrap1 1-1
| | | | pieceInnWrap2 0-1
| | | | pieceOutWrap 0-1
- end choose -
| | | | pieceCut 0-99
| | | | serialN 1-9
| | | | @numberingOrg [Optional]
| | | | @idQualifier [Optional]
| | | | pieceLength 0-1
| | | | @um [Optional] [Default= MTR]
| | | | pieceWeight 0-1
| | | | @um [Optional] [Default= KGM]
- or -
| | | | piece 0-99
| | | | @endUse [Optional]
| | | | serialN 0-9
| | | | @numberingOrg [Optional]
| | | | @idQualifier [Optional]
| | | | EPC 0-1
| | | | @numberingOrg [Optional]
| | | | @TID [Optional]
| | | | totFault 0-1
| | | | pieceStatus 0-1
| | | | pieceLength 0-1
| | | | @um [Optional] [Default= MTR]
| | | | pieceWidth 0-1
| | | | @um [Optional] [Default= CMT]
| | | | pieceCutWidth 0-1
| | | | @um [Optional] [Default= CMT]
| | | | pieceWeight 0-1
| | | | @um [Optional] [Default= KGM]
| | | | pieceWeightM 0-1

```

```

| | | | @um [Optional] [Default= GRM]
| | | | grossWeight 0-1
| | | | @um [Required]
| | | | pieceAllow 0-1
| | | | @um [Required]
| | | | lotN 0-2
| | | | @numberingOrg [Optional]
| | | | dyeN 0-1
| | | | @numberingOrg [Optional]
| | | | mixMatch 0-1
| | | | @numberingOrg [Optional]
| | | | packageN 0-1
| | | | @numberingOrg [Optional]
| | | | @packageContainerN [Optional]
| | | | piecePack 0-1
- choose -
| | | | | piecePackText 1-1
- or -
| | | | | pieceInnWrap1 1-1
| | | | | pieceInnWrap2 0-1
| | | | | pieceOutWrap 0-1
- end choose -
- end choose -
| | | | note 0-99
| | | | @numberingOrg [Optional]
| | | | @codeList [Optional]
| | | | @noteLabel [Optional]
qty 1-3
@um [Required]
price 0-1
@um [Optional]
@priceQualifier [Optional] [Default= NET]
@currency [Optional]
deliveryDate 0-1
@dateForm [Optional]
thirdParty 0-3
@VAT [Optional]
@role [Required]
@sender [Optional]
| | | | id 1-1
| | | | @numberingOrg [Optional]
| | | | legalName 0-1
| | | | dept 0-1
| | | | subDept 0-1
| | | | person 0-1
| | | | @email [Optional]
| | | | @phone [Optional]
| | | | @fax [Optional]
| | | | street 0-1
| | | | city 0-1
| | | | subCountry 0-1
| | | | country 0-1
| | | | postCode 0-1
fabricComponent 1-9
| | | | texCode 1-1
| | | | @numberingOrg [Optional]
| | | | | art 1-1
| | | | | @numberingOrg [Optional]
| | | | | @codeList [Optional]
| | | | | @listName [Optional]
| | | | | @listVersion [Optional]

```

```

| | | | pattern 0-1
| | | |   @numberingOrg [Optional]
| | | |   @codeList [Optional]
| | | |   @listName [Optional]
| | | |   @listVersion [Optional]
| | | | color 0-1
| | | |   @numberingOrg [Optional]
| | | |   @codeList [Optional]
| | | |   @listName [Optional]
| | | |   @listVersion [Optional]
| | | | added 0-9
| | | |   @numberingOrg [Optional]
| | | |   @addType [Optional]
| | | | description 0-unbounded
| | | |   @ln [Optional]
| | | | qty 1-3
| | | |   @um [Required]
- choose -
| | | | serialN 0-unbounded
| | | |   @numberingOrg [Optional]
| | | |   @idQualifier [Optional]
- or -
| | | | itemsList 0-unbounded
| | | |   qualityLevel 0-1
| | | |   @numberingOrg [Optional]
| | | |   @codeList [Optional]
| | | |   @listName [Optional]
| | | |   @listVersion [Optional]
| | | |   itemIdentification 1-unbounded
| | | |     serialN 1-9
| | | |     @numberingOrg [Optional]
| | | |     @idQualifier [Optional]
- end choose -
| | | | refDoc 0-1
| | | |   @docType [Required]
| | | |   docID 1-2
| | | |   @numberingOrg [Optional]
| | | |   docDate 0-1
| | | |   @dateForm [Optional]
| | | |   season 0-1
| | | |   @numberingOrg [Optional]
| | | |   @codeList [Optional]
| | | |   @listName [Optional]
| | | |   @listVersion [Optional]
| | | |   itemID 0-1
| | | |   attachment 0-1
| | | |     @uid [Optional]
| | | |     fileName 0-1
| | | |     @numberingOrg [Optional]
| | | |     binaryObject 0-1
| | | |     @format [Optional]
| | | |     @mime [Optional]
| | | |     @encoding [Optional]
| | | |     @characterSet [Optional]
| | | |     externalReference 0-99
| | | |       uri 1-1
| | | |       @isURL [Optional] [Default= true]
| | | |       mimeTypeCode 0-1
| | | |       formatCode 0-1
| | | |       encodingCode 0-1
| | | |       characterSetCode 0-1

```

```

| | | | location 0-1
| | | |   @LRI [Optional]
| | | | note 0-99
| | | |   @numberingOrg [Optional]
| | | |   @codeList [Optional]
| | | |   @noteLabel [Optional]
| | | | fabPrintOperation 1-9
| | | |   fabPrintTech 1-1
| | | |   dyeStuff 0-1
| | | |   fabPrintSpecs 0-9
| | | |   - choose -
| | | |     | fabPrintCharText 1-1
| | | |   - or -
| | | |     | fabPrintChar 1-1
| | | |   - end choose -
| | | |     | specValue 0-1
| | | |     |   @um [Optional]
| | | |     |   @source [Optional]
| | | |     |   @method [Optional]
| | | |     |   @application [Optional]
| | | |     |   @CV [Optional]
| | | |   groundColor 0-9
| | | |     @numberingOrg [Optional]
| | | |     @screenN [Required]
| | | |   refDoc 0-1
| | | |     @docType [Required]
| | | |     | docID 1-2
| | | |     |   @numberingOrg [Optional]
| | | |     | docDate 0-1
| | | |     |   @dateForm [Optional]
| | | |     | season 0-1
| | | |     |   @numberingOrg [Optional]
| | | |     |   @codeList [Optional]
| | | |     |   @listName [Optional]
| | | |     |   @listVersion [Optional]
| | | |     | itemID 0-1
| | | |     | attachment 0-1
| | | |     |   @uid [Optional]
| | | |     |   | fileName 0-1
| | | |     |   |   @numberingOrg [Optional]
| | | |     |   | binaryObject 0-1
| | | |     |   |   @format [Optional]
| | | |     |   |   @mime [Optional]
| | | |     |   |   @encoding [Optional]
| | | |     |   |   @characterSet [Optional]
| | | |     |   | externalReference 0-99
| | | |     |   |   | uri 1-1
| | | |     |   |   |   @isURL [Optional] [Default= true]
| | | |     |   |   |   mimeTypeCode 0-1
| | | |     |   |   |   formatCode 0-1
| | | |     |   |   |   encodingCode 0-1
| | | |     |   |   |   characterSetCode 0-1
| | | |     | note 0-99
| | | |     |   @numberingOrg [Optional]
| | | |     |   @codeList [Optional]
| | | |     |   @noteLabel [Optional]
| | | |   dtScheme 0-1
| | | |     @taxType [Required]
| | | |     | taxCategory 0-1
| | | |     | taxRate 0-1
| | | |     | legalRef 0-1

```

| | | | | |
|--|--|--|--|--------------------------|
| | | | | @codeList [Required] |
| | | | | note 0-99 |
| | | | | @numberingOrg [Optional] |
| | | | | @codeList [Optional] |
| | | | | @noteLabel [Optional] |

2.2 Detailed description of document elements

Following tables show all elements (complex and simple) used in this document. Description includes: 1) element's information: xml tag, name, brief description, data type and syntax constraints; 2) information about use of the element in a particular position in the document: xpath and possible associated notes.

2.2.1 Complex elements (Aggregate Business Information Entities)

Complex elements are those elements whose content is composed of other elements (childs). Complex elements are alphabetically ordered.

| | |
|--------------------------|---|
| allowanceCharge | Allowances and Charges related to an Order or a contract (XPath <code>TEXPrintOrder/terms/allowanceCharge</code>) 0-9 |
| attachment | an attached document. An attachment can refer to an external document or be included with the document being exchanged (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/attachment</code>) 0-1 (XPath <code>TEXPrintOrder/TPCOheader/refDoc/attachment</code>) 0-1 (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/attachment</code>) 0-1 |
| buyer | details of the Buyer (party that buys the good or service that is object of the current collaborative process) - base type: Nad, (XPath <code>TEXPrintOrder/TPCOheader/buyer</code>) 1-1 |
| dtScheme | set of data usable to declare the duty or tax applied (XPath <code>TEXPrintOrder/terms/allowanceCharge/dtScheme</code>) 0-1 (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/dtScheme</code>) 0-1 |
| externalReference | details about an external object, such as a document stored at a remote location (XPath <code>TEXPrintOrder/TPCOheader/refDoc/attachment/externalReference</code>) 0-99 (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/attachment/externalReference</code>) 0-99 (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/attachment/externalReference</code>) 0-99 |
| fabPrintOperation | details of a fabric printing operation (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation</code>) 1-9 |
| fabPrintSpecs | technical specifications of a fabric printing operation (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/fabPrintSpecs</code>) 0-9 |
| fabricComponent | identification details of a fabric used in a sub-contracted manufacturing operation (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricComponent</code>) 1-9 |
| fabricCompos | composition of the fabric according to the Directory 97/37/CE (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricProd/fabricCompos</code>) 0-1 |
| fabricProd | manufacturing specifications of the product to be obtained from an operation of the sub-contracted production of fabric (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricProd</code>) 1-1 |
| fabricSpecs | technical characteristics of fabric, linked either to an operation of subcontracted production or to the purchase (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricProd/fabricSpecs</code>) 0-99 |
| insPayment | payment details for payment by installments (XPath <code>TEXPrintOrder/terms/insPayment</code>) 0-5 - note: <i>excluded the case of offers, this set of data is alternative to payment set and must be iterated for each payment installment</i> |

| | |
|---------------------------|---|
| itemIdentification | serial identification of a product unit (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/itemsList/itemIdentification) 1-unbounded - note: <i>identification of the single product unit contained in the list</i> |
| itemsList | list of the single product units (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/itemsList) 0-unbounded - note: <i>it may be used to identify the pieces/chains that the Subcontractor must use for the commissioned work with multiple serial Ids for each one</i> |
| payment | payment details for payment all in one (XPath TEXPrintOrder/terms/payment) 0-5 - note: <i>excluded the case of offers, this set of data is alternative to insPayment, it can be iterated to specify alternative terms of payment (e.g.: 60 days or 30 days with 3% discount)</i> |
| piece | Identification data and measurement of the fabric piece. (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece) 0-99 |
| pieceChain | identification data and measurements of a chain of pieces still to be cut (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain) 0-99 |
| pieceCut | identification data and measurements of a fabric piece belonging to a chain still to be cut (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/pieceCut) 0-99 - note: <i>here the data of the pieces making up the chain should be specified</i> |
| piecePack | type of wrapping or packing of the fabric pieces (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/piecePack) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/piecePack) 0-1 |
| refDoc | identification of a document and of an item thereof, to which the message makes reference (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc) 0-1 - note: <i>here the delivery documents can be specified</i> (XPath TEXPrintOrder/TPCOheader/refDoc) 0-9 |
| subContractor | details of the Sub-contractor - base type: Nad, (XPath TEXPrintOrder/TPCOheader/subContractor) 1-1 |
| terms | details of the commercial obligations for payment and delivery (XPath TEXPrintOrder/terms) 0-1 |
| texCode | full codification of the textile product (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/texCode) 1-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/texCode) 1-1 |
| thirdParty | details of the Third Party, different from Buyer or Supplier - base type: Nad, (XPath TEXPrintOrder/TPCOheader/thirdParty) 0-5 - note: <i>here the Party to whom the Subcontractor must send the semi-finished products for subsequent operations can be specified</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/thirdParty) 0-3 - note: <i>here the Party to whom the Subcontractor must send the semi-finished product for subsequent operations can be specified</i> |
| TPCObody | body of the document TEXTILE PRINTING COMMISSION ORDER (XPath TEXPrintOrder/TPCObody) 1-1 |
| TPCOheader | header of the document TEXTILE PRINTING COMMISSION ORDER (XPath TEXPrintOrder/TPCOheader) 1-1 |

| | |
|------------------|--|
| TPCOitem | line of the document TEXTILE PRINTING COMMISSION ORDER (XPath TEXPrintOrder/TPCObody/TPCOitem) 1-unbounded |
| trade | general terms of trade for the specified supply (XPath TEXPrintOrder/terms/trade) 0-1 |
| transInfo | details of transport: mode, carrier and delivery place (XPath TEXPrintOrder/terms/transInfo) 0-5 |

2.2.2 Simple elements (Basic Business Information Entities)

Simple elements are those elements whose content is characterized by a data type plus a domain of possible values. Simple elements are alphabetically ordered.

| | |
|-----------------------------|---|
| AC_amount | amount of an Allowance or Charge - base type: decimal, fraction digits: 2, (XPath TEXPrintOrder/terms/allowanceCharge/AC_amount) 1-1 |
| AC_category | coded specification of an Allowance or Charge - base type: string, cod. table: T41 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T41.xml (XPath TEXPrintOrder/terms/allowanceCharge/AC_category) 1-1 |
| AC_categoryText | free text description of an Allowance or Charge - base type: string, max length: 250, (XPath TEXPrintOrder/terms/allowanceCharge/AC_categoryText) 1-1 |
| AC_percent | amount of an Allowance or Charge as a percentage - base type: decimal, max inclusive: 100, fraction digits: 2, (XPath TEXPrintOrder/terms/allowanceCharge/AC_percent) 1-1 |
| added | additional code of the product (complementing the formers) - base type: string, max length: 80, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/texCode/added) 0-9 - note: <i>here an additional codification (see table T44) can be specified</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/texCode/added) 0-9 - note: <i>here an additional codification (see table T44) can be specified</i> |
| additionalIdentifier | additional identification code of a Party, for example customs registries or others - base type: string, max length: 15, (XPath TEXPrintOrder/TPCOheader/buyer/additionalIdentifier) 0-9 - note: <i>identifiers for example for exports, such as MID (Manufacturer Identification Code), EORI (E.O.R.I. - Economic Operator Registration and Identification)</i> |
| @addType | qualifier of the additional coding of a product - base type: string, cod. table: T44 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T44.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/texCode/added/@addType) [Optional] - nota: <i>addType allows the clarification of the meaning of the added element content; it is strongly suggested to use it always.</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/texCode/added/@addType) [Optional] - nota: <i>addType allows the clarification of the meaning of the added element content; it is strongly suggested to use it always.</i> |
| @application | force or similar condition (e.g. no. of revolutions) applied in a test as specified within the standard - base type: string, max length: 15, |

| | |
|------------------|---|
| | <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/fabricSpecs/specValue/@application) [Optional]</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/fabPrintSpecs/specValue/@application) [Optional]</p> |
| art | <p>article number of the product</p> <p>- base type: string, max length: 80,</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/texCode/art) 1-1</p> <p>- note: <i>can be used either for the base-article (excluding pattern/colour) or for the SKU</i></p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/texCode/art) 1-1</p> <p>- note: <i>can be used either for the base-article (excluding pattern/colour) or for the SKU</i></p> |
| binaryObject | <p>a binary large object containing an attached document</p> <p>- base type: base64Binary,</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/attachment/binaryObject) 0-1</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/attachment/binaryObject) 0-1</p> <p>(XPath TEXPrintOrder/TPCOheader/refDoc/attachment/binaryObject) 0-1</p> |
| carrier | <p>identification of the transport carrier</p> <p>- base type: string, max length: 40,</p> <p>(XPath TEXPrintOrder/terms/transInfo/carrier) 0-1</p> |
| @characterSet | <p>the character set of the binary object if the mime type is text</p> <p>- base type: normalizedString,</p> <p>(XPath TEXPrintOrder/TPCOheader/refDoc/attachment/binaryObject/@characterSet) [Optional]</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/attachment/binaryObject/@characterSet) [Optional]</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/attachment/binaryObject/@characterSet) [Optional]</p> |
| characterSetCode | <p>the character set of an external document</p> <p>- base type: normalizedString,</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/attachment/externalReference/characterSetCode) 0-1</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/attachment/externalReference/characterSetCode) 0-1</p> <p>(XPath TEXPrintOrder/TPCOheader/refDoc/attachment/externalReference/characterSetCode) 0-1</p> |
| city | <p>name of the city (town, village)</p> <p>- base type: string, max length: 40,</p> <p>(XPath TEXPrintOrder/TPCOheader/subContractor/city) 0-1</p> <p>(XPath TEXPrintOrder/TPCOheader/buyer/city) 0-1</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/thirdParty/city) 0-1</p> <p>(XPath TEXPrintOrder/TPCOheader/thirdParty/city) 0-1</p> |
| @codeList | <p>it specifies the URL where the list of codes used to make an instance of the element can be found</p> <p>- base type: string, max length: 255,</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/texCode/art/@codeList) [Optional]</p> <p>- nota: <i>this attribute should be ALTERNATIVE to the others</i></p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/texCode/pattern/@codeList) [Optional]</p> <p>- nota: <i>this attribute should be ALTERNATIVE to the others</i></p> <p>(XPath TEXPrintOrder/TPCOheader/note/@codeList) [Optional]</p> <p>- nota: <i>must be used to provide (URL) the list of codes used in "noteLabel"</i></p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/note/@codeList) [Optional]</p> <p>- nota: <i>must be used to provide (URL) the list of codes used in "noteLabel"</i></p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/dtScheme/note/@codeList) [Optional]</p> <p>- nota: <i>must be used to provide (URL) the list of codes used in "noteLabel"</i></p> |

| | |
|-----------|--|
| | <p>(XPath TEXPrintOrder/TPCOheader/season/@codeList) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/note/@codeList) [Optional] - nota: <i>must be used to provide (URL) the list of codes used in "noteLabel"</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/season/@codeList) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/dtScheme/legalRef/@codeList) [Required] (XPath TEXPrintOrder/terms/allowanceCharge/dtScheme/legalRef/@codeList) [Required] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/texCode/pattern/@codeList) [Optional] - nota: <i>this attribute should be ALTERNATIVE to the others</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/note/@codeList) [Optional] - nota: <i>must be used to provide (URL) the list of codes used in "noteLabel"</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/season/@codeList) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/texCode/art/@codeList) [Optional] - nota: <i>this attribute should be ALTERNATIVE to the others</i> (XPath TEXPrintOrder/terms/allowanceCharge/dtScheme/note/@codeList) [Optional] - nota: <i>must be used to provide (URL) the list of codes used in "noteLabel"</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/texCode/color/@codeList) [Optional] - nota: <i>this attribute could be used as alternative to the others</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/texCode/color/@codeList) [Optional] - nota: <i>this attribute could be used as alternative to the others</i> (XPath TEXPrintOrder/TPCOheader/refDoc/season/@codeList) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/itemsList/qualityLevel/@codeList) [Optional]</p> |
| color | <p>colour number of the product, when not included in the model or fabric code - base type: string, max length: 15, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/texCode/color) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/texCode/color) 0-1</p> |
| country | <p>code of the nation - base type: string, cod. table: T10 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T10.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/thirdParty/country) 0-1 (XPath TEXPrintOrder/TPCOheader/thirdParty/country) 0-1 (XPath TEXPrintOrder/TPCOheader/buyer/country) 0-1 (XPath TEXPrintOrder/TPCOheader/subContractor/country) 0-1</p> |
| @CTest | <p>indicates the need to execute a colour test before the operation - base type: string, cod. table: NT38 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT38.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/@CTest) [Optional]</p> |
| @currency | <p>currency in which a specified monetary data is expressed - base type: string, cod. table: T9 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T9.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/price/@currency) [Optional] - nota: <i>Currency referred by the price.</i> (XPath TEXPrintOrder/terms/allowanceCharge/@currency) [Optional]</p> |
| @CV | <p>coefficient of variation (CV) of a measurement - base type: decimal, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/fabPrintSpecs/specValue/@CV) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/fabricSpecs/specValue/@CV) [Optional]</p> |

| | |
|------------------|--|
| @dateForm | <p>format used for the date</p> <ul style="list-style-type: none"> - base type: string, cod. table: NT29 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT29.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/deliveryDate/@dateForm) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/docDate/@dateForm) [Optional] (XPath TEXPrintOrder/terms/transInfo/delEffectiveDate/@dateForm) [Optional] (XPath TEXPrintOrder/terms/transInfo/despatchDate/@dateForm) [Optional] (XPath TEXPrintOrder/TPCOheader/msgDate/@dateForm) [Optional] (XPath TEXPrintOrder/TPCOheader/refDoc/docDate/@dateForm) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/docDate/@dateForm) [Optional] |
| delEffectiveDate | <p>effective date of delivery of goods (declared in Despatch), according to one of the patterns YYYY-MM-DD, YYYY-MM-DD:HH-MM or YYYY-WW.</p> <ul style="list-style-type: none"> - base type: string, (XPath TEXPrintOrder/terms/transInfo/delEffectiveDate) 0-1 |
| deliveryDate | <p>date of delivery of goods, requested or promised in the purchase process, according to one of the patterns YYYY-MM-DD, YYYY-MM-DD:HH-MM or YY YY-WW.</p> <ul style="list-style-type: none"> - base type: string, (XPath TEXPrintOrder/TPCObody/TPCOitem/deliveryDate) 0-1 |
| deliveryPlace | <p>place of delivery of goods, ultimate or related to a given leg</p> <ul style="list-style-type: none"> - base type: string, max length: 250, (XPath TEXPrintOrder/terms/transInfo/deliveryPlace) 0-1 |
| dept | <p>name or code of a contact department within a Party</p> <ul style="list-style-type: none"> - base type: string, max length: 40, (XPath TEXPrintOrder/TPCOheader/thirdParty/dept) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/thirdParty/dept) 0-1 (XPath TEXPrintOrder/TPCOheader/buyer/dept) 0-1 (XPath TEXPrintOrder/TPCOheader/subContractor/dept) 0-1 |
| description | <p>free text description. The content of the element must be unique, it might be translated and repeated into more languages (thus no more than one instance for each language).</p> <ul style="list-style-type: none"> - base type: string, max length: 250, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/texCode/description) 0-unbounded - note: <i>Product description</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/texCode/description) 0-unbounded - note: <i>Product description</i> |
| despatchDate | <p>date of despatch of goods, requested or promised in the purchase process, according to one of the patterns YYYY-MM-DD, YYYY-MM-DD:HH-MM or YYY YYY-WW.</p> <ul style="list-style-type: none"> - base type: string, (XPath TEXPrintOrder/terms/transInfo/despatchDate) 0-1 |
| despatchPlace | <p>place of despatch of goods, origin or related to a given leg</p> <ul style="list-style-type: none"> - base type: string, max length: 250, (XPath TEXPrintOrder/terms/transInfo/despatchPlace) 0-1 |
| docDate | <p>date of issue of the referenced document, according to one of the patterns YYY YYY-MM-DD, YYYY-MM-DD:HH-MM or YYYY-WW.</p> <ul style="list-style-type: none"> - base type: string, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/docDate) 0-1 (XPath TEXPrintOrder/TPCOheader/refDoc/docDate) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/docDate) 0-1 |

| | |
|--------------|---|
| docID | <p>identification number of the referenced document SINCE 2008-1 ITS USE I N THE HEADER IS DISCOURAGED (REPLACED BY msgID)</p> <p>- base type: string, max length: 80,</p> <p>(XPath TEXPrintOrder/TPCOheader/docID) 0-1 (XPath TEXPrintOrder/TPCOheader/refDoc/docID) 1-2 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/docID) 1-2 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/docID) 1-2</p> |
| @docType | <p>type or class to which the referenced document belongs</p> <p>- base type: string, cod. table: T21 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T21.xml (XPath TEXPrintOrder/TPCOheader/refDoc/@docType) [Required] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/@docType) [Required] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/@docType) [Required]</p> |
| dyeN | <p>number of the dying batch of a textile product</p> <p>- base type: string, max length: 15,</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/dyeN) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/dyeN) 0-1</p> |
| dyeStuff | <p>dye stuff used in the fabric dye process</p> <p>- base type: string, cod. table: T16 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T16.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/dyeStuff) 0-1</p> |
| @email | <p>electronic mail address of the contact person within a Party</p> <p>- base type: string, max length: 250,</p> <p>(XPath TEXPrintOrder/TPCOheader/thirdParty/person/@email) [Optional] (XPath TEXPrintOrder/TPCOheader/subContractor/person/@email) [Optional] (XPath TEXPrintOrder/TPCOheader/buyer/person/@email) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/thirdParty/person/@email) [Optional]</p> |
| @encoding | <p>specifies the decoding algorithm of the binary object</p> <p>- base type: normalizedString,</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/attachment/binaryObject/@encoding) [Optional] (XPath TEXPrintOrder/TPCOheader/refDoc/attachment/binaryObject/@encoding) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/attachment/binaryObject/@encoding) [Optional]</p> |
| encodingCode | <p>the encoding/decoding algorithm used with the external object</p> <p>- base type: normalizedString,</p> <p>(XPath TEXPrintOrder/TPCOheader/refDoc/attachment/externalReference/encodingCode) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/attachment/externalReference/encodingCode) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/attachment/externalReference/encodingCode) 0-1</p> |
| @endUse | <p>specifies the final use of the fabric</p> <p>- base type: string, cod. table: NT4 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT4.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/@endUse) [Optional]</p> |
| EPC | <p>serial identifier used for tracing a physical item with RFID technology</p> <p>- base type: string,</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/EPC) 0-1</p> <p>- note: <i>the use of this element is DEPRECATED, use the appropriate elements (serialN)</i></p> |

| | |
|------------------|---|
| fabPrintChar | code specifying a characteristic or parameter of the fabric printing - base type: string, cod. table: T45 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T45.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/ fabPrintSpecs/fabPrintChar) 1-1 |
| fabPrintCharText | free text describing a characteristic or parameter of the fabric printing - base type: string, max length: 250, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/ fabPrintSpecs/fabPrintCharText) 1-1 |
| fabPrintTech | operation technology used for fabric printing - base type: string, cod. table: T264 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T264.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/fabPrintTech) 1-1 |
| fabricChar | code of the physical or mechanical parameter used to define a "technical characteristic of the fabric" (see Fabric technical sheet) - base type: string, cod. table: T13 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T13.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/ fabricSpecs/fabricChar) 1-1 |
| fabricCharText | free text describing the physical or mechanical parameter used to define a "technical characteristic of the fabric" - base type: string, max length: 80, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/ fabricSpecs/fabricCharText) 1-1 |
| fabricWidth | width of the fabric as technical specification - base type: decimal, min inclusive: 0, fraction digits: 2, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/fabricWidth) 0-1 |
| @fax | fax number of the contact person within a Party - base type: string, max length: 35, (XPath TEXPrintOrder/TPCOheader/thirdParty/person/@fax) [Optional] (XPath TEXPrintOrder/TPCOheader/buyer/person/@fax) [Optional] (XPath TEXPrintOrder/TPCOheader/subContractor/person/@fax) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/thirdParty/person/@fax) [Optional] |
| @fibre | type of fibre used in a textile product - base type: string, cod. table: T19 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T19.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/ fabricCompos/percCompos/@fibre) [Required] |
| fileName | unique identifier (name) of the file - base type: string, max length: 255, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/ refDoc/attachment/fileName) 0-1 (XPath TEXPrintOrder/TPCOheader/refDoc/attachment/fileName) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/ refDoc/attachment/fileName) 0-1 |
| @finDiscount | financial discount rate applied for payment by the date specified - base type: decimal, min inclusive: 0, max inclusive: 100, fraction digits: 2, (XPath TEXPrintOrder/terms/payment/@finDiscount) [Optional] |
| @finSurcharge | financial surcharge rate applied for payment after the date specified - base type: decimal, min inclusive: 0, max inclusive: 100, fraction digits: 2, (XPath TEXPrintOrder/terms/payment/@finSurcharge) [Optional] |
| @format | the format of the binary content - base type: string, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/ refDoc/attachment/binaryObject/@format) [Optional] (XPath TEXPrintOrder/TPCOheader/refDoc/attachment/ binaryObject/@format) [Optional] |

| | |
|--------------|--|
| | (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/attachment/binaryObject/@format</code>) [Optional] |
| formatCode | <p>the format of the external object</p> <ul style="list-style-type: none"> - base type: normalizedString, <p>(XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/attachment/externalReference/formatCode</code>) 0-1</p> <p>(XPath <code>TEXPrintOrder/TPCOheader/refDoc/attachment/externalReference/formatCode</code>) 0-1</p> <p>(XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/attachment/externalReference/formatCode</code>) 0-1</p> |
| grossWeight | <p>the gross weight, declared for transport or customs purpose</p> <ul style="list-style-type: none"> - base type: decimal, min inclusive: 0, fraction digits: 2, <p>(XPath <code>TEXPrintOrder/terms/transInfo/grossWeight</code>) 0-1</p> <p>(XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/grossWeight</code>) 0-1</p> <ul style="list-style-type: none"> - note: <i>gross Weight is related to the weight of the piece after packing.</i> |
| groundColor | <p>ground colour related to a printing screen</p> <ul style="list-style-type: none"> - base type: string, max length: 15, <p>(XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/groundColor</code>) 0-9</p> |
| id | <p>primary identification code of a Party; it is recommended the format: nation code (ISO 3166) + VAT identification number (11 crt), with the qualifier "numberingOrg"= MF</p> <ul style="list-style-type: none"> - base type: string, max length: 15, <p>(XPath <code>TEXPrintOrder/TPCObody/TPCOitem/thirdParty/id</code>) 1-1</p> <p>(XPath <code>TEXPrintOrder/TPCOheader/thirdParty/id</code>) 1-1</p> <p>(XPath <code>TEXPrintOrder/TPCOheader/subContractor/id</code>) 1-1</p> <p>(XPath <code>TEXPrintOrder/TPCOheader/buyer/id</code>) 1-1</p> |
| @idQualifier | <p>Qualification of the identifier.</p> <ul style="list-style-type: none"> - base type: string, <p>(XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/serialN/@idQualifier</code>) [Optional]</p> <ul style="list-style-type: none"> - nota: <i>this attribute should be used when the numberingOrg attribute is not enough to declare the type of serial identifier</i> <p>(XPath <code>TEXPrintOrder/TPCOheader/buyer/additionalIdentifier/@idQualifier</code>) [Optional]</p> <ul style="list-style-type: none"> - nota: <i>this attribute should be used when the numberingOrg attribute is not enough to declare the type of identifier</i> <p>(XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/pieceCut/serialN/@idQualifier</code>) [Optional]</p> <ul style="list-style-type: none"> - nota: <i>this attribute should be used when the numberingOrg attribute is not enough to declare the type of serial identifier</i> <p>(XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/itemsList/itemIdentification/serialN/@idQualifier</code>) [Optional]</p> <ul style="list-style-type: none"> - nota: <i>this attribute should be used when the numberingOrg attribute is not enough to declare the type of serial identifier</i> <p>(XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/serialN/@idQualifier</code>) [Optional]</p> <ul style="list-style-type: none"> - nota: <i>this attribute should be used when the numberingOrg attribute is not enough to declare the type of serial identifier</i> <p>(XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/serialN/@idQualifier</code>) [Optional]</p> <ul style="list-style-type: none"> - nota: <i>this attribute should be used when the numberingOrg attribute is not enough to declare the type of serial identifier</i> |
| incoTerm | <p>specification of the terms of trade (INCOTERMS)</p> <ul style="list-style-type: none"> - base type: string, cod. table: T3 <p>http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T3.xml</p> <p>(XPath <code>TEXPrintOrder/terms/trade/incoTerm</code>) 1-1</p> |
| incoTermText | <p>free text specifying the terms of trade (incoterm, location)</p> <ul style="list-style-type: none"> - base type: string, max length: 250, |

| | |
|-----------|---|
| | (XPath TEXPrintOrder/terms/trade/incoTermText) 1-1 |
| @isURL | <p>it indicates if the referred element is an URL (true) or not (false)</p> <p>- base type: boolean, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/attachment/externalReference/uri/@isURL) [Optional] [Default= true]</p> <p>- nota: <i>usage of URLs is recommended</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/attachment/externalReference/uri/@isURL) [Optional] [Default= true]</p> <p>- nota: <i>usage of URLs is recommended</i> (XPath TEXPrintOrder/TPCOheader/refDoc/attachment/externalReference/uri/@isURL) [Optional] [Default= true]</p> <p>- nota: <i>usage of URLs is recommended</i></p> |
| itemID | <p>number of the line/item of the referenced document</p> <p>- base type: string, max length: 6, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/itemID) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/itemID) 0-1 (XPath TEXPrintOrder/TPCOheader/refDoc/itemID) 0-1</p> |
| legalName | <p>legal name of a Party</p> <p>- base type: string, max length: 250, (XPath TEXPrintOrder/TPCObody/TPCOitem/thirdParty/legalName) 0-1 (XPath TEXPrintOrder/TPCOheader/thirdParty/legalName) 0-1 (XPath TEXPrintOrder/TPCOheader/buyer/legalName) 0-1 (XPath TEXPrintOrder/TPCOheader/subContractor/legalName) 0-1</p> |
| legalRef | <p>legal reference of the duty or tax or fee category</p> <p>- base type: string, (XPath TEXPrintOrder/TPCObody/TPCOitem/dtScheme/legalRef) 0-1 (XPath TEXPrintOrder/terms/allowanceCharge/dtScheme/legalRef) 0-1</p> |
| lineN | <p>number of the line item of the present message (xml document); it is set by the role that produces the document. Usually it is a progressive number, but not always.</p> <p>- base type: positiveInteger, min inclusive: 1, max inclusive: 9999, (XPath TEXPrintOrder/TPCObody/TPCOitem/lineN) 1-1</p> |
| @listName | <p>the name of the list of codes used to make an instance of the element (it might be thought as descriptive element, i.e. 'fabric printing technologies', or not, i.e. "T264")</p> <p>- base type: string, max length: 40, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/texCode/pattern/@listName) [Optional]</p> <p>- nota: <i>this attribute should always be used coupled with "numberingOrg"</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/texCode/art/@listName) [Optional]</p> <p>- nota: <i>this attribute should always be used coupled with "numberingOrg"</i> (XPath TEXPrintOrder/TPCOheader/season/@listName) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/texCode/color/@listName) [Optional]</p> <p>- nota: <i>this attribute should always be used coupled with "numberingOrg"</i> (XPath TEXPrintOrder/TPCOheader/refDoc/season/@listName) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/itemsList/qualityLevel/@listName) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/texCode/color/@listName) [Optional]</p> <p>- nota: <i>this attribute should always be used coupled with "numberingOrg"</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/season/@listName) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/texCode/pattern/@listName) [Optional]</p> <p>- nota: <i>this attribute should always be used coupled with "numberingOrg"</i></p> |

| | |
|--------------|--|
| | <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/ texCode/art/@listName) [Optional]</p> <p>- nota: <i>this attribute should always be used coupled with “numberingOrg”</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/ refDoc/season/@listName) [Optional]</p> |
| @listVersion | <p>it specifie the version of the list of codes used to make an instance of the element</p> <p>- base type: string, max length: 6, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/ refDoc/season/@listVersion) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/ texCode/color/@listVersion) [Optional]</p> <p>- nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath TEXPrintOrder/TPCOheader/season/@listVersion) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/ itemsList/qualityLevel/@listVersion) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/ texCode/pattern/@listVersion) [Optional]</p> <p>- nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/ texCode/art/@listVersion) [Optional]</p> <p>- nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/ texCode/pattern/@listVersion) [Optional]</p> <p>- nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/ texCode/color/@listVersion) [Optional]</p> <p>- nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/ refDoc/season/@listVersion) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/ texCode/art/@listVersion) [Optional]</p> <p>- nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath TEXPrintOrder/TPCOheader/refDoc/season/@listVersion) [Optional]</p> |
| @ln | <p>Language code.</p> <p>- base type: string, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/ texCode/description/@ln) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/ texCode/description/@ln) [Optional]</p> |
| location | <p>specification of a location</p> <p>- base type: string, max length: 40, (XPath TEXPrintOrder/terms/trade/location) 0-1</p> <p>- note: <i>place to which the INCOTERM applies</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/location) 0-1</p> <p>- note: <i>it may be used to specify the location where lie the pieces that the Subcontractor must use for the commissioned work operation</i></p> |
| @logo | <p>company logo (URL of the image jpeg or gif). It is recommended that the width of the image does not exceed 640 pixel.</p> <p>- base type: string, max length: 255, (XPath TEXPrintOrder/TPCOheader/buyer/@logo) [Optional]</p> |
| lotN | <p>lot number of a product or batch number of the raw material</p> <p>- base type: string, max length: 15, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/lotN) 0-2</p> <p>- note: <i>The lotN instances must differ by value of the numberingOrg attribute</i></p> |

| | |
|--------------|---|
| | (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/lotN) 0-1 |
| @LRI | attribute usable to format a string according to a customized User rule (local rule) - base type: string, cod. table: NT3 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT3.xml (XPath TEXPrintOrder/terms/trade/location/@LRI) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/location/@LRI) [Optional] |
| @maxQty | maximum product quantity - base type: decimal, min inclusive: 0, fraction digits: 2, (XPath TEXPrintOrder/terms/allowanceCharge/@maxQty) [Optional] - nota: <i>maximum quantity of product for the application of this allowance or charge</i> |
| @method | standard protocol or method employed in a test to evaluate a characteristic or a parameter - base type: string, max length: 80, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/fabricSpecs/specValue/@method) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/fabPrintSpecs/specValue/@method) [Optional] |
| @mime | the mime type of the binary object - base type: normalizedString, (XPath TEXPrintOrder/TPCOheader/refDoc/attachment/binaryObject/@mime) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/attachment/binaryObject/@mime) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/attachment/binaryObject/@mime) [Optional] |
| mimeCode | mime type of the external object - base type: normalizedString, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/attachment/externalReference/mimeCode) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/attachment/externalReference/mimeCode) 0-1 (XPath TEXPrintOrder/TPCOheader/refDoc/attachment/externalReference/mimeCode) 0-1 |
| @minQty | minimum product quantity - base type: decimal, min inclusive: 0, fraction digits: 2, (XPath TEXPrintOrder/terms/allowanceCharge/@minQty) [Optional] - nota: <i>minimum quantity of product for the application of this allowance or charge</i> |
| mixMatch | colour hue used for the match of garments - base type: string, max length: 15, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/mixMatch) 0-1 |
| msgCurrency | currency used to express the monetary amounts of the message - base type: string, cod. table: T9 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T9.xml (XPath TEXPrintOrder/TPCOheader/msgCurrency) 0-1 |
| msgDate | date of issue of the present message (xml document), according to one of the patterns YYYY-MM-DD, YYYY-MM-DD:HH-MM or YYYY-WW. - base type: string, (XPath TEXPrintOrder/TPCOheader/msgDate) 1-1 |
| @msgfunction | function performed by the present message with regards to the transmission - base type: string, cod. table: NT18 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT18.xml (XPath TEXPrintOrder/@msgfunction) [Optional] [Default= OR] |

| | |
|---------------|--|
| msgID | key identifier of the business document in the information system of the issuing Party. In case of more despatches of the same business document, it is unchanged. - base type: string, max length: 35, (XPath TEXPrintOrder/TPCOheader/msgID) 0-1 |
| msgN | identification number given to the message (xml document) by its issuer. In case of more despatches of the same business document, it changes. - base type: string, max length: 35, (XPath TEXPrintOrder/TPCOheader/msgN) 1-1 |
| netWeight | the net weight declared for transport or customs purpose - base type: decimal, min inclusive: 0, fraction digits: 2, (XPath TEXPrintOrder/terms/transInfo/netWeight) 0-1 |
| note | free text or structured (computer processing) note. For note structuring use the attributes "noteLabel" and "codelist" - base type: string, max length: 350, (XPath TEXPrintOrder/TPCObody/TPCOitem/dtScheme/note) 0-99 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/note) 0-99 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/note) 0-99 (XPath TEXPrintOrder/TPCOheader/note) 0-99 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/note) 0-99 (XPath TEXPrintOrder/terms/allowanceCharge/dtScheme/note) 0-99 |
| @noteLabel | subject qualifier of a note - base type: string, max length: 35, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/note/@noteLabel) [Optional] - nota: <i>must be used to qualify the subject of the note</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/note/@noteLabel) [Optional] - nota: <i>must be used to qualify the subject of the note</i> (XPath TEXPrintOrder/TPCOheader/note/@noteLabel) [Optional] - nota: <i>must be used to qualify the subject of the note</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/note/@noteLabel) [Optional] - nota: <i>must be used to qualify the subject of the note</i> (XPath TEXPrintOrder/terms/allowanceCharge/dtScheme/note/@noteLabel) [Optional] - nota: <i>must be used to qualify the subject of the note</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/dtScheme/note/@noteLabel) [Optional] - nota: <i>must be used to qualify the subject of the note</i> |
| @numberingOrg | code specifying the organisation who has created or owns the coding or numbering system - base type: string, cod. table: NT6 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT6.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/season/@numberingOrg) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/note/@numberingOrg) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/thirdParty/id/@numberingOrg) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/docID/@numberingOrg) [Optional] - nota: <i>here can be specified whose document numbering is used (e.g.: Client, Supplier, ..)</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/note/@numberingOrg) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/serialN/@numberingOrg) [Optional] - nota: <i>here the issuer of the serial number must be specified (when different from the Supplier)</i> |

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/
texCode/pattern/@numberingOrg) [Optional]

- nota: *this attribute should be used either single or coupled with "listName" and "listVersion"*

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/
itemsList/qualityLevel/@numberingOrg) [Optional]

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/
refDoc/attachment/fileName/@numberingOrg) [Optional]

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/
groundColor/@numberingOrg) [Optional]

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/
texCode/color/@numberingOrg) [Optional]

- nota: *this attribute should be used either single or coupled with "listName" and "listVersion"*

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/
texCode/added/@numberingOrg) [Optional]

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/
refDoc/attachment/fileName/@numberingOrg) [Optional]

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/
texCode/@numberingOrg) [Optional]

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/
refDoc/docID/@numberingOrg) [Optional]

- nota: *here can be specified whose document numbering is used (e.g.: Client, Supplier, ..)*

(XPath TEXPrintOrder/TPCObody/TPCOitem/dtScheme/note/@numberingOrg) [Optional]

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/
note/@numberingOrg) [Optional]

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/
refDoc/season/@numberingOrg) [Optional]

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/
itemsList/itemIdentification/serialN/@numberingOrg) [Optional]

- nota: *here the issuer of the serial number must be specified (when different from the Supplier)*

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/
texCode/art/@numberingOrg) [Optional]

- nota: *this attribute should be used either single or coupled with "listName" and "listVersion"*

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/
texCode/color/@numberingOrg) [Optional]

- nota: *this attribute should be used either single or coupled with "listName" and "listVersion"*

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/
texCode/pattern/@numberingOrg) [Optional]

- nota: *this attribute should be used either single or coupled with "listName" and "listVersion"*

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/
piece/serialN/@numberingOrg) [Optional]

- nota: *here the issuer of the serial number must be specified (when different from the Supplier)*

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/
piece/EPC/@numberingOrg) [Optional]

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/
texCode/art/@numberingOrg) [Optional]

- nota: *this attribute should be used either single or coupled with "listName" and "listVersion"*

(XPath TEXPrintOrder/terms/allowanceCharge/dtScheme/note/@numberingOrg) [Optional]

(XPath TEXPrintOrder/TPCOheader/subContractor/id/@numberingOrg) [Optional]

(XPath TEXPrintOrder/TPCOheader/refDoc/season/@numberingOrg) [Optional]

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/texCode/@numberingOrg) [Optional]

(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/
pieceChain/dyeN/@numberingOrg) [Optional]

(XPath TEXPrintOrder/TPCOheader/buyer/id/@numberingOrg) [Optional]

| | |
|--------------------|---|
| | <p>(XPath TEXPrintOrder/TPCOheader/buyer/additionalIdentifier/@numberingOrg) [Optional]</p> <p>- nota: <i>here the issuer of the identifier must be specified</i></p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/lotN/@numberingOrg) [Optional]</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/serialN/@numberingOrg) [Optional]</p> <p>- nota: <i>here the issuer of the serial number must be specified (when different from the Supplier)</i></p> <p>(XPath TEXPrintOrder/TPCOheader/refDoc/attachment/fileName/@numberingOrg) [Optional]</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/texCode/added/@numberingOrg) [Optional]</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/packageN/@numberingOrg) [Optional]</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/pieceCut/serialN/@numberingOrg) [Optional]</p> <p>- nota: <i>here the issuer of the serial number must be specified (when different from the Supplier)</i></p> <p>(XPath TEXPrintOrder/TPCOheader/season/@numberingOrg) [Optional]</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/lotN/@numberingOrg) [Optional]</p> <p>(XPath TEXPrintOrder/TPCOheader/refDoc/docID/@numberingOrg) [Optional]</p> <p>- nota: <i>here can be specified whose document numbering is used (e.g.: Client, Supplier, ..)</i></p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/packageN/@numberingOrg) [Optional]</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/dyeN/@numberingOrg) [Optional]</p> <p>(XPath TEXPrintOrder/TPCOheader/docID/@numberingOrg) [Optional]</p> <p>- nota: <i>here can be specified whose document numbering is used (e.g.: Client, Supplier, ..)</i></p> <p>(XPath TEXPrintOrder/TPCOheader/thirdParty/id/@numberingOrg) [Optional]</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/mixMatch/@numberingOrg) [Optional]</p> <p>(XPath TEXPrintOrder/TPCOheader/note/@numberingOrg) [Optional]</p> |
| @packageContainerN | <p>reference usable to indicate the outer package containing this package</p> <p>- base type: string, max length: 40,</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/packageN/@packageContainerN) [Optional]</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/packageN/@packageContainerN) [Optional]</p> |
| packageN | <p>serial number used to identify a transport package</p> <p>- base type: string, max length: 40,</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/packageN) 0-1</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/packageN) 0-1</p> <p>- note: <i>here the transport package containing the piece can be identified</i></p> |
| @part | <p>percent fraction of a total payment</p> <p>- base type: decimal, min inclusive: 1, max inclusive: 99, fraction digits: 2,</p> <p>(XPath TEXPrintOrder/terms/insPayment/@part) [Required]</p> <p>- nota: <i>here the % value of each installment must be indicated</i></p> |
| pattern | <p>pattern/design number of the product, when not included in the article code</p> <p>- base type: string, max length: 15,</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/texCode/pattern) 0-1</p> <p>(XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/texCode/pattern) 0-1</p> |
| payMode | <p>way or means of payment</p> <p>- base type: string, cod. table: T2</p> <p>http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T2.xml</p> <p>(XPath TEXPrintOrder/terms/insPayment/payMode) 0-1</p> |

| | |
|---------------|---|
| | (XPath TEXPrintOrder/terms/payment/payMode) 0-1 |
| payTerm | code specifying the terms or time by which the payment must be done - base type: string, cod. table: T1 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T1.xml (XPath TEXPrintOrder/terms/payment/payTerm) 1-1 (XPath TEXPrintOrder/terms/insPayment/payTerm) 1-1 |
| payTermText | free text specifying the terms by which the payment must be done (time/mode or means) - base type: string, max length: 250, (XPath TEXPrintOrder/terms/payment/payTermText) 1-1 (XPath TEXPrintOrder/terms/insPayment/payTermText) 1-1 |
| pcTolerance | percent deviation tolerated on the value of a measurement (it must have a plus or minus sign) - base type: decimal, min inclusive: 0, max inclusive: 100, total digits: 2, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/fabricSpecs/pcTolerance) 0-2 |
| percCompos | fiber rate in the product composition - base type: decimal, min inclusive: 0, max inclusive: 100, fraction digits: 2, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/fabricCompos/percCompos) 1-9 |
| person | name of the contact person within a Party - base type: string, max length: 40, (XPath TEXPrintOrder/TPCObody/TPCOitem/thirdParty/person) 0-1 (XPath TEXPrintOrder/TPCOheader/buyer/person) 0-1 (XPath TEXPrintOrder/TPCOheader/subContractor/person) 0-1 (XPath TEXPrintOrder/TPCOheader/thirdParty/person) 0-1 |
| @phone | phone number of the contact person within a Party - base type: string, max length: 35, (XPath TEXPrintOrder/TPCOheader/buyer/person/@phone) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/thirdParty/person/@phone) [Optional] (XPath TEXPrintOrder/TPCOheader/subContractor/person/@phone) [Optional] (XPath TEXPrintOrder/TPCOheader/thirdParty/person/@phone) [Optional] |
| pieceAllow | allowance required or accorded for the piece - base type: decimal, fraction digits: 2, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/pieceAllow) 0-1 |
| pieceCutWidth | effective usable width of the fabric piece (for garment manufacturing) - base type: decimal, min inclusive: 0, fraction digits: 2, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/pieceCutWidth) 0-1 |
| pieceInnWrap1 | code specifying the type of inner wrapping/packing used for the fabric piece - base type: string, cod. table: T4 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T4.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/piecePack/pieceInnWrap1) 1-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/piecePack/pieceInnWrap1) 1-1 |
| pieceInnWrap2 | code sub-specifying the type of inner wrapping/packing used for the fabric piece - base type: string, cod. table: T5 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T5.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/piecePack/pieceInnWrap2) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/piecePack/pieceInnWrap2) 0-1 |
| pieceLength | length of the piece - base type: decimal, min inclusive: 0, fraction digits: 2, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/pieceLength) 0-1 |

| | |
|-----------------|--|
| | (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/pieceCut/pieceLength) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/pieceLength) 0-1 |
| pieceOutWrap | code specifying the type of outer wrapping or packing used for the fabric piece - base type: string, cod. table: T6 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T6.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/piecePack/pieceOutWrap) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/piecePack/pieceOutWrap) 0-1 |
| piecePackText | free text specifying the type of wrapping or packing used for the fabric piece - base type: string, max length: 250, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/piecePack/piecePackText) 1-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/piecePack/piecePackText) 1-1 |
| pieceStatus | code used to describe the status of a fabric piece after the control - base type: string, cod. table: T52 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T52.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/pieceStatus) 0-1 |
| pieceWeight | effective total weight of the fabric piece - base type: decimal, min inclusive: 0, fraction digits: 2, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/pieceWeight) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/pieceWeight) 0-1 - note: <i>It is the net weight of the piece.</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/pieceCut/pieceWeight) 0-1 |
| pieceWeightM | effective weight per metre of the fabric piece - base type: decimal, min inclusive: 0, fraction digits: 2, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/pieceWeightM) 0-1 |
| pieceWidth | effective width of the fabric piece - base type: decimal, min inclusive: 0, fraction digits: 2, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/pieceWidth) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/pieceWidth) 0-1 |
| postCode | code defining the postal zone - base type: string, max length: 10, (XPath TEXPrintOrder/TPCOheader/buyer/postCode) 0-1 (XPath TEXPrintOrder/TPCOheader/thirdParty/postCode) 0-1 (XPath TEXPrintOrder/TPCOheader/subContractor/postCode) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/thirdParty/postCode) 0-1 |
| price | unit price of the article, object or service specified - base type: decimal, min inclusive: 0, fraction digits: 4, (XPath TEXPrintOrder/TPCObody/TPCOitem/price) 0-1 |
| @priceQualifier | type of price with reference to discount and taxes - base type: string, cod. table: NT20 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT20.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/price/@priceQualifier) [Optional] [Default= NET] |
| @productLevel | level of the product (end or intermediate) yielded by an operation in a work cycle - base type: string, cod. table: NT22 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT22.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/@productLevel) [Optional] [Default= END] |

| | |
|--------------|--|
| | - nota: <i>this qualifier "intermediate" must be used when the product is also a component in an other line of the same Commission Order</i> |
| @progr | progressive number in the sequence - base type: positiveInteger, min inclusive: 1, (XPath TEXPrintOrder/terms/transInfo/@progr) [Optional] - nota: <i>Indicates the position of the leg in a sequence of transport legs.</i> |
| qty | net quantity of the article or object correlated, qualified by the function of the document (ordering, delivering, ..) and by the context - base type: decimal, min inclusive: 0, fraction digits: 2, (XPath TEXPrintOrder/TPCObody/TPCOitem/qty) 1-3 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/qty) 1-3 - note: <i>quantity to be consumed in the transformation. This element can have more instances only if the units of measure are different</i> |
| qualityLevel | the product quality level (first choice, second choice,...). - base type: string, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/itemsList/qualityLevel) 0-1 |
| @role | Third Party role qualifier - base type: string, cod. table: NT2 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT2.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/thirdParty/@role) [Required] (XPath TEXPrintOrder/TPCOheader/thirdParty/@role) [Required] |
| @screenN | identification number of a printing screen - base type: positiveInteger, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/groundColor/@screenN) [Required] |
| season | sale season; defined as: season (1 crt) + year (4 crt) - season: S/S=1 A/W=2 Spring=3 Summer=4 Autumn=5 Winter=6: for more than four seasons use alphabetic sequence: 1st season=A 2nd season=B etc.etc. - base type: string, max length: 15, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/season) 0-1 - note: <i>here indicates the season to which the referenced document belongs</i> (XPath TEXPrintOrder/TPCOheader/refDoc/season) 0-1 - note: <i>here indicates the season to which the referenced document belongs</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/season) 0-1 - note: <i>here indicates the season to which the referenced document belongs</i> (XPath TEXPrintOrder/TPCOheader/season) 0-1 |
| @sender | qualifier that specifies the Party issuing of the document - base type: boolean, (XPath TEXPrintOrder/TPCOheader/buyer/@sender) [Optional] - nota: <i>This attribute is mandatory when the STYLESHEET must be used</i> (XPath TEXPrintOrder/TPCOheader/subContractor/@sender) [Optional] - nota: <i>This attribute is mandatory when the STYLESHEET must be used</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/thirdParty/@sender) [Optional] - nota: <i>This attribute is mandatory when the STYLESHEET must be used</i> (XPath TEXPrintOrder/TPCOheader/thirdParty/@sender) [Optional] - nota: <i>This attribute is mandatory when the STYLESHEET must be used</i> |
| serialN | serial number used for the identification of a physical unit - base type: string, max length: 250, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/itemsList/itemIdentification/serialN) 1-9 <hr/> AAAA-WARNING! - text not AVAILABLE n. 245 - In=en - note: <i>multiple values of serialN are allowed for different representations of the serial identifier of the same product unit. Instances of serialN must differ at least for one value of numberingOrg and idQualifier.</i> (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/serialN) 0-9 <hr/> |

| | |
|-------------|--|
| | <p>AAAA-WARNING! - text not AVAILABLE n. 245 - In=en</p> <p>- note: multiple values of serialN are allowed for different representations of the serial identifier of the same piece. Instances of serialN must differ at least for one value of numberingOrg and idQualifier. (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/serialN) 1-9</p> <p>- note: multiple values of serialN are allowed in order to provide different representations of the serial identifier of the same piece chain. Different instances of serialN must differ at least for one value of idQualifier or numberingOrg (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/pieceCut/serialN) 1-9</p> <p>- note: multiple values of serialN are allowed in order to provide different representations of the serial identifier of the same piece. Different instances of serialN must differ at least for one value of idQualifier or numberingOrg (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/serialN) 0-unbounded</p> <p>- note: it may be used to identify the pieces/chains that the Subcontractor must use for the commissioned work</p> |
| @source | <p>party who has provided the data</p> <p>- base type: string, cod. table: NT12 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT12.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/fabPrintSpecs/specValue/@source) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/fabricSpecs/specValue/@source) [Optional]</p> |
| specValue | <p>value requested for a property or a parameter that is measured</p> <p>- base type: decimal, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/fabricSpecs/specValue) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/fabPrintSpecs/specValue) 0-1</p> |
| street | <p>street and building number identifying a location</p> <p>- base type: string, max length: 80, (XPath TEXPrintOrder/TPCOheader/thirdParty/street) 0-1 (XPath TEXPrintOrder/TPCOheader/subContractor/street) 0-1 (XPath TEXPrintOrder/TPCOheader/buyer/street) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/thirdParty/street) 0-1</p> |
| subCountry | <p>short name or code of the sub-country entity</p> <p>- base type: string, max length: 9, (XPath TEXPrintOrder/TPCOheader/thirdParty/subCountry) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/thirdParty/subCountry) 0-1 (XPath TEXPrintOrder/TPCOheader/subContractor/subCountry) 0-1 (XPath TEXPrintOrder/TPCOheader/buyer/subCountry) 0-1</p> |
| subDept | <p>name or code of a contact department within a Party</p> <p>- base type: string, max length: 40, (XPath TEXPrintOrder/TPCOheader/subContractor/subDept) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/thirdParty/subDept) 0-1 (XPath TEXPrintOrder/TPCOheader/buyer/subDept) 0-1 (XPath TEXPrintOrder/TPCOheader/thirdParty/subDept) 0-1</p> |
| taxCategory | <p>duty or tax or fee category</p> <p>- base type: string, cod. table: T62 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T62.xml (XPath TEXPrintOrder/terms/allowanceCharge/dtScheme/taxCategory) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/dtScheme/taxCategory) 0-1</p> |
| taxRate | <p>duty or tax or fee percent rate</p> <p>- base type: string, (XPath TEXPrintOrder/terms/allowanceCharge/dtScheme/taxRate) 0-1 (XPath TEXPrintOrder/TPCObody/TPCOitem/dtScheme/taxRate) 0-1</p> |
| @taxType | <p>duty or tax or fee type</p> <p>- base type: string, cod. table: T61 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T61.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/dtScheme/@taxType) [Required] (XPath TEXPrintOrder/terms/allowanceCharge/dtScheme/@taxType) [Required]</p> |

| | |
|--------------------|---|
| @TID | serial number wired into the RFID chip - base type: string, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/ piece/EPC/@TID) [Optional] |
| tolerance | deviation tolerated on the value of a measurement (it must have a plus or minus sign) - base type: decimal, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/ fabricSpecs/tolerance) 0-2 |
| totFault | total number of faults: the 1st/2nd digit count the "Large faults", the 3rd/4th the "Medium faults" and the 5th/6th the "Small faults" - base type: positiveInteger, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/totFault) 0-1 |
| transCondition | special condition of transport or special service requested to the Forwarder - base type: string, cod. table: T38 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T38.xml (XPath TEXPrintOrder/terms/transInfo/transCondition) 0-3 |
| transConditionText | free text description of the special condition of transport or special service requested to the Forwarder - base type: string, max length: 250, (XPath TEXPrintOrder/terms/transInfo/transConditionText) 0-1 |
| transMeans | means of transport, in general or referred to a specific leg - base type: string, cod. table: T40 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T40.xml (XPath TEXPrintOrder/terms/transInfo/transMeans) 0-1 |
| transMode | way of transport, in general or referred to the specified leg - base type: string, cod. table: T8 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T8.xml (XPath TEXPrintOrder/terms/transInfo/transMode) 1-1 |
| @transReason | reason for the transport - base type: string, cod. table: NT11 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT11.xml (XPath TEXPrintOrder/terms/transInfo/@transReason) [Optional] |
| @uid | unique element identifier within the xml document - base type: string, (XPath TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/ refDoc/attachment/@uid) [Optional] (XPath TEXPrintOrder/TPCOheader/refDoc/attachment/@uid) [Optional] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/ refDoc/attachment/@uid) [Optional] |
| @um | specification of the unit of measure - base type: string, cod. table: NT7 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT7.xml (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/ pieceChain/pieceCut/pieceWeight/@um) [Optional] [Default= KGM] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/ piece/pieceLength/@um) [Optional] [Default= MTR] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/ piece/pieceWidth/@um) [Optional] [Default= CMT] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/ pieceChain/pieceCut/pieceLength/@um) [Optional] [Default= MTR] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/ pieceChain/pieceWidth/@um) [Optional] [Default= CMT] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/ pieceChain/pieceWeight/@um) [Optional] [Default= KGM] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/ qty/@um) [Required] (XPath TEXPrintOrder/TPCObody/TPCOitem/fabricProd/ piece/pieceAllow/@um) [Required] |

| | |
|-------------|---|
| | <p>(XPath <code>TEXPrintOrder/TPCObody/TPCOitem/price/@um</code>) [Optional] - nota: <i>Unit of measure of the product to which the price is referred (price per meter)</i></p> <p>(XPath <code>TEXPrintOrder/TPCObody/TPCOitem/qty/@um</code>) [Required] (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/grossWeight/@um</code>) [Required] (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/pieceCutWidth/@um</code>) [Optional] [Default= CMT] (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/pieceWeight/@um</code>) [Optional] [Default= KGM] (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/pieceWeightM/@um</code>) [Optional] [Default= GRM] (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricProd/fabricWidth/@um</code>) [Optional] [Default= CMT] (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricProd/fabricSpecs/specValue/@um</code>) [Optional] (XPath <code>TEXPrintOrder/terms/allowanceCharge/@um</code>) [Optional] (XPath <code>TEXPrintOrder/terms/transInfo/netWeight/@um</code>) [Required] (XPath <code>TEXPrintOrder/terms/transInfo/grossWeight/@um</code>) [Required] (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/fabPrintSpecs/specValue/@um</code>) [Optional] (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricProd/pieceChain/pieceLength/@um</code>) [Optional] [Default= MTR] (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricProd/fabricSpecs/tolerance/@um</code>) [Required] (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricProd/fabricSpecs/pcTolerance/@um</code>) [Optional] - nota: <i>to be used when it has to be soecified if the declared percentage is by weight, volume, etc...</i></p> |
| uri | <p>Uniform Resource Identifier (URI) that identifies the external object as an Internet resource - base type: <code>normalizedString</code>, (XPath <code>TEXPrintOrder/TPCOheader/refDoc/attachment/externalReference/uri</code>) 1-1 (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabPrintOperation/refDoc/attachment/externalReference/uri</code>) 1-1 (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/refDoc/attachment/externalReference/uri</code>) 1-1</p> |
| @useProfile | <p>use profile to which the present document is compliant if it was agreed by the parties. It is suggested a URI with reference to the firms or the URL of the profile. - base type: <code>string</code>, (XPath <code>TEXPrintOrder/@useProfile</code>) [Optional]</p> |
| @VAT | <p>VAT rate or code (DEPRECATED, use <code>dtScheme</code> element) - base type: <code>string</code>, cod. table: NT16 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT16.xml (XPath <code>TEXPrintOrder/TPCOheader/thirdParty/@VAT</code>) [Optional] (XPath <code>TEXPrintOrder/terms/allowanceCharge/@VAT</code>) [Optional] (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/lineN/@VAT</code>) [Optional] - nota: <i>Deprecated, prefer dtScheme when available.</i> (XPath <code>TEXPrintOrder/TPCObody/TPCOitem/thirdParty/@VAT</code>) [Optional]</p> |
| @version | <p>Dictionary version from which the instance has been created - base type: <code>string</code>, cod. table: NT100 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT100.xml (XPath <code>TEXPrintOrder/@version</code>) [Optional] [Default= draft]</p> |

2.3 Suggested best practices

TEXPrintOrder/TPCObody/TPCOitem/fabricComponent/

itemsList/itemIdentification/serialN (serial number used for the identification of a physical unit)

in the case of garment with RFID for anti-counterfeiting, RFID EPCGlobal for logistics and NFC for the customer experience there should be three serial elements with pairs of attributes numberingOrg/idQualifier: "CL"/"RFID", "GS1"/"RFID", "CL"/"NFC".

TEXPrintOrder/TPCObody/TPCOitem/fabricProd/piece/serialN (serial number used for the identification of a physical unit)

This element might contain also codes for RFID devices.

2.4 Enumeration tables

List of enumeration tables used in the XML document. You can find the corresponding codes at:
<http://www.ebiz-tcf.eu/moda-ml/imple/moda-ml-draft.asp?lingua=en&pag=6>

NT100 - eBIZ TCFUpstream version
NT11 - transport causal
NT12 - data source
NT16 - VAT rate or code
NT18 - message function
NT2 - third party qualifier
NT20 - price qualifier
NT22 - product type of an operation
NT29 - format of a date
NT3 - data format
NT38 - colour test
NT4 - end use
NT6 - coding system owner/issuer
NT7 - unit of measure
T1 - terms of payment
T10 - ISO3166 - Country
T13 - CFM properties of fabric
T16 - dyestuff type
T19 - fibre type
T2 - Modes of payment
T21 - type of document
T264 - fabric printing technology
T3 - terms of delivery
T38 - transport conditions
T4 - fabric piece inner packing (wrapping) 1
T40 - type of transport means
T41 - type of Allowance or Charge
T44 - additional code type
T45 - fabric print parameter type
T5 - fabric piece inner packing (wrapping) 2
T52 - fabric piece status
T6 - fabric piece outer packing
T61 - duty or tax or fee type
T62 - duty or tax or fee category
T8 - Modes of Transport
T9 - ISO4217 - Currency

ACKNOWLEDGEMENT



This action is part of the eBIZ-4.0 project, which has received funding from the European Union's COSME Programme (2014 - 2020).




DISCLAIMER



The content of this document represents the views of the authors only and is their sole responsibility; it cannot be considered to reflect the views of the European Commission and/or the Executive Agency for Small and Medium-sized Enterprises (EASME) or any other body of the European Union.



The European Commission and the Agency do not accept any responsibility for use that may be made of the information it contains.

Annex A

Representative images of the principal complex elements' structure.







Annex B

NT100 - eBIZ TCFUpstream version

dictionary version

Agency name: eBIZ

tabella cod.: NT100

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT100.xml

| Code | Description | Adoption note | Date of insertion |
|--------|-------------|---------------|-------------------|
| 2013-1 | v2013-1 | | 01/07/2013 |
| 2018-1 | v2018-1 | | 04/11/2018 |
| draft | draft | | 08/09/2017 |

NT11 - transport causal

reason for the transport

Agency name: eBIZ

tabella cod.: NT11

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT11.xml

| Code | Description | Adoption note | Date of insertion |
|------|-----------------------|---------------|-------------------|
| FOC | free of charge | | |
| FRW | return from re-works | | |
| FST | return from storage | | |
| FWW | return from view | | |
| FWK | return from works | | |
| IST | in storage | | |
| NWK | return non-worked | | |
| RJC | return from rejection | | |
| SEL | to sell | | |
| STO | to storage | | |
| VEW | to view | | |
| WRK | to works | | |

NT12 - data source

party who has provided the data

Agency name: eBIZ

tabella cod.: NT12

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT12.xml

| Code | Description | Adoption note | Date of insertion |
|------|---------------------|---------------|-------------------|
| AC | internal test | | |
| CO | external test | | |
| CV | test after steaming | | |

NT16 - VAT rate or code

VAT rate or code (DEPRECATED, use dtScheme element)

tabella cod.: NT16

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT16.xml

NT18 - message function

function performed by the present message with regards to the transmission

Agency name: eBIZ

tabella cod.: NT18

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT18.xml

| Code | Description | Adoption note | Date of insertion |
|------|-------------------------------------|---------------|-------------------|
| CA | delete this document | | 01/07/2013 |
| CP | copy | | |
| OR | original | | |
| RC | re-transmission for data correction | | |
| RT | re-transmission | | |

NT2 - third party qualifier

Third Party role qualifier

Agency name: eBIZ

tabella cod.: NT2

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT2.xml

| Code | Description | Adoption note | Date of insertion |
|------|--------------------------------------|---------------|-------------------|
| AG | Sales Agent | | |
| CO | Quality Controller | | |
| DC | Response to | | |
| DF | Invoicee | | |
| DI | Copy to (CC) | | 28/10/2014 |
| DM | Consignee | | |
| DP | Consignment address (Delivery Party) | | |
| IM | Importer | | |
| OR | Originator | | 10/09/2014 |
| SP | Forwarder | | |
| TX | Tax Representative | | |

NT20 - price qualifier

type of price with reference to discount and taxes

Agency name: eBIZ

tabella cod.: NT20

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT20.xml

| Code | Description | Adoption note | Date of insertion |
|------|-----------------------|---------------|-------------------|
| GET | gross excluding taxes | | |
| GIT | gross including taxes | | |
| NET | net excluding taxes | | |
| NIT | net including taxes | | |

NT22 - product type of an operation

level of the product (end or intermediate) yielded by an operation in a work cycle

Agency name: eBIZ

tabella cod.: NT22

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT22.xml

| Code | Description | Adoption note | Date of insertion |
|------|--------------|---------------|-------------------|
| END | end-product | | |
| INT | intermediate | | |

NT29 - format of a date

format used for the date

Agency name: eBIZ

tabella cod.: NT29

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT29.xml

| Code | Description | Adoption note | Date of insertion |
|------|------------------|---------------|-------------------|
| D | YYYY-MM-DD | | |
| M | YYYY-MM-DD:HH-MM | | |
| W | YYYY-WW | | |

NT3 - data format

format of a string according to a customized User rule (local rule)

Agency name: eBIZ

tabella cod.: NT3

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT3.xml

| Code | Description | Adoption note | Date of insertion |
|------|-----------------|---------------|-------------------|
| EN4 | GS1-GLN | | 01/07/2013 |
| MD | mutually agreed | | |

NT38 - colour test

specification of colour test before the operation

tabella cod.: NT38

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT38.xml

| Code | Description | Adoption note | Date of insertion |
|------|------------------|---------------|-------------------|
| 1 | only colour test | | |
| 2 | with colour test | | |

NT4 - end use

specifies the final use of the product

Agency name: eBIZ

tabella cod.: NT4

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT4.xml

| Code | Description | Adoption note | Date of insertion |
|------|--------------|---------------|-------------------|
| PC | test piece | | |
| PR | production | | |
| SA | Sample | | 10/09/2014 |
| SC | samples card | | |
| TI | patch | | |
| TP | (test cut) | | |

NT6 - coding system owner/issuer

code specifying the organisation who has created or owns the coding or numbering system

Agency name: eBIZ

tabella cod.: NT6

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT6.xml

| Code | Description | Adoption note | Date of insertion |
|------|------------------------------|---------------|-------------------|
| CL | Customer/buyer | | |
| CO | Quality Controller | | |
| EN | GS1 (ex-EAN International) | | |
| ES | e-Stockflow | | |
| FO | Supplier | | |
| GS | GS1 | | 01/07/2013 |
| MF | VAT identifier | | |
| ML | Moda-ML | | |
| SP | Service Provider | | |

NT7 - unit of measure

specification of the unit of measure, it is a sub set of table Unit of Measure Code - UN/ECE REC 20 delivered by United Nations Economic Commission for Europe (UN/ECE)

Agency name: eBIZ / UN/ECE

tabella cod.: NT7

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT7.xml

Other link: <http://docs.oasis-open.org/ubl/os-UBL-2.1/cl/gc/default/UnitOfMeasureCode-2.1.gc#>

| Code | Description | Adoption note | Date of insertion |
|-------------|--------------------|----------------------|--------------------------|
| CMK | square centimetre | | 20/12/2017 |
| CMQ | cubic centimetre | | 20/12/2017 |
| CMT | centimetre | | |
| CNE | centiNewton | | |
| CO2TON | ton of CO2 | | 10/09/2014 |
| COUPLES | couples | | |
| DMQ | cubic decimetre | | |
| E37 | pixel | | 11/04/2018 |
| GRM | gram | | |
| HUR | hour | | |
| INH | inch | | |
| KGM | kilogram | | |
| KMT | kilometer | | |
| KWH | kilowatthours | | 10/09/2014 |
| LBR | pound | | |
| MIN | minute | | |
| MMK | centimetre | | 20/12/2017 |
| MMK | square millimetre | | 20/12/2017 |
| MTK | square metre | | 20/12/2017 |
| MTQ | cubic metre | | |
| MTR | metre | | |
| NMB | numero | | |
| ONZ | ounce | | |
| P1 | percent | | |
| PPM | parts per milion | | |
| PZ | piece | | |
| RPM | rounds per metre | | |
| YRD | yard | | |

T1 - terms of payment

code specifying the terms or time by which the payment must be done

Agency name: eBIZ

tabella cod.: T1

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T1.xml

| Code | Description | Adoption note | Date of insertion |
|----------------|--|---------------|-------------------|
| ANTICIP | PAYMENT IN ADVANCE | | |
| BLCOLLECT/120D | BILL OF LADING 120 DD | | |
| BLCOLLECT/30D | BILL OF LADING 30 DD | | |
| BLCOLLECT/60D | BILL OF LADING 60 DD | | |
| BLCOLLECT/90D | BILL OF LADING 90 DD | | |
| CASH | PAYMENT ON DELIVERY | | |
| CASHINV | PAYMENT ON RECEIPT OF INVOICE | | |
| CREDOC/0D | DOCUMENTARY CREDIT FOR PAYM. AT SIGHT | | |
| CREDOC/120 | DOCUMENTARY CREDIT FOR PAYM. AT 120 DD | | |
| CREDOC/150 | DOCUMENTARY CREDIT FOR PAYM. AT 150 DD | | |
| CREDOC/180 | DOCUMENTARY CREDIT FOR PAYM. AT 180 DD | | |
| CREDOC/30D | DOCUMENTARY CREDIT FOR PAYM. AT 30 DD | | |
| CREDOC/45D | DOCUMENTARY CREDIT FOR PAYM. AT 45 DD | | |
| CREDOC/60 | DOCUMENTARY CREDIT FOR PAYM. AT 60 DD | | |
| CREDOC/90 | DOCUMENTARY CREDIT FOR PAYM. AT 90 DD | | |
| DEL/10 | PAYMENT AT 10 DD AFTER DELIVERY | | |
| DOCOLLECT/120D | DOCUMENTARY COLLECTION AT 120 DD | | |
| DOCOLLECT/30D | DOCUMENTARY COLLECTION AT 30 DD | | |
| DOCOLLECT/60D | DOCUMENTARY COLLECTION AT 60 DD | | |
| DOCOLLECT/90D | DOCUMENTARY COLLECTION AT 90 DD | | |
| INV/120D | PAYMENT AT 120 DD AFTER RECEIPT OF INVOICE | | |
| INV/150D | PAYMENT AT 150 DD AFTER RECEIPT OF INVOICE | | |
| INV/180D | PAYMENT AT 180 DD AFTER RECEIPT OF INVOICE | | |
| INV/30D | PAYMENT AT 30 DD AFTER RECEIPT OF INVOICE | | |
| INV/45D | PAYMENT AT 45 DD AFTER RECEIPT OF INVOICE | | |
| INV/60D | PAYMENT AT 60 DD AFTER RECEIPT OF INVOICE | | |
| INV/90D | PAYMENT AT 90 DD AFTER RECEIPT OF INVOICE | | |

| | | | |
|----------------|---|--|--|
| INVULTIMO | PAYMENT AT END MONTH RECEIPT INVOICE | | |
| INVULTIMO/10D | PAYMENT 10 DD AFTER END MONTH RECEIPT INVOICE | | |
| INVULTIMO/120D | PAYMENT 120 DD AFTER END MONTH RECEIPT INVOICE | | |
| INVULTIMO/150D | PAYMENT 150 DD AFTER END MONTH RECEIPT INVOICE | | |
| INVULTIMO/180D | PAYMENT 180 DD AFTER END MONTH RECEIPT INVOICE | | |
| INVULTIMO/240D | PAYMENT 240 DD AFTER END MONTH RECEIPT INVOICE | | |
| INVULTIMO/30D | PAYMENT 30 DD AFTER END MONTH RECEIPT INVOICE | | |
| INVULTIMO/45D | PAYMENT 45 DD AFTER END MONTH RECEIPT INVOICE | | |
| INVULTIMO/60D | PAYMENT 60 DD AFTER END MONTH RECEIPT INVOICE | | |
| INVULTIMO/90D | PAYMENT 90 DD AFTER END MONTH RECEIPT INVOICE | | |
| NOPAY | WITHOUT PAYMENT | | |
| RECREDOC/0D | IRREVOC. DOCUMENTARY CREDIT FOR PAYM. AT SIGHT | | |
| RECREDOC/120D | IRREVOC. DOCUMENTARY CREDIT FOR PAYM. AT 120 DD | | |
| RECREDOC/150D | IRREVOC. DOCUMENTARY CREDIT FOR PAYM. AT 150 DD | | |
| RECREDOC/180D | IRREVOC. DOCUMENTARY CREDIT FOR PAYM. AT 180 DD | | |
| RECREDOC/30D | IRREVOC. DOCUMENTARY CREDIT FOR PAYM. AT 30 DD | | |
| RECREDOC/45D | IRREVOC. DOCUMENTARY CREDIT FOR PAYM. AT 45 DD | | |
| RECREDOC/60D | IRREVOC. DOCUMENTARY CREDIT FOR PAYM. AT 60 DD | | |
| RECREDOC/90D | IRREVOC. DOCUMENTARY CREDIT FOR PAYM. AT 90 DD | | |
| ULTIMO | PAYMENT BY END MONTH OF DELIVERY | | |
| ULTIMO/10 | PAYMENT AT 10 DD AFTER END MONTH OF DELIVERY | | |

T10 - ISO3166 - Country

code of the nation

Agency name: ISO

tabella cod.: T10

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T10.xml

Table not printed: there are 239 elements, more than the maximum specified for printing: 99.

T13 - CFM properties of fabric

code of the physical or mechanical parameter used to define a "technical characteristic of the fabric" (see Fabric technical sheet)

tabella cod.: T13

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T13.xml

| Code | Description | Adoption note | Date of insertion |
|------|--|---------------|-------------------|
| CMA | resistance to pilling (UNI.E.1512434) | | |
| CMB | seam slippage - warp (NFG7117) | | |
| CMC | seam slippage - weft (NFG7117) | | |
| CMD | breaking strength - warp (ISO 1394-1) | | |
| CME | breaking strength - weft (ISO 1394-1) | | |
| CMF | resistance to abrasion (EN 12947) | | |
| CMH | tear strength (ISO 9290) | | |
| CMI | crease recovery (ISO 9867) | | |
| CMJ | elongation - warp (BS 4294/68) | | |
| CMK | elongation - weft (BS 4294/68) | | |
| CML | tear resistance - warp | | |
| CMM | tear resistance - weft | | |
| CMN | resistance to bending | | |
| CMP | spray test | | |
| SLA | colour fastness to light (ISO 105-B02) | | |
| SLB | colour fastness to washing (ISO 105-C06) | | |
| SLC | colour fastness to dry cleaning (ISO 105-D01) | | |
| SLD | colour fastness to spotting water (ISO 105-E07) | | |
| SLG | colour fastness to alkaline perspiration (ISO 105-E04) | | |
| SLH | colour fastness to acid perspiration (ISO 105-E04) | | |
| SLI | colour fastness to dry rubbing (ISO 105-X12) | | |
| SLJ | colour fastness to wet rubbing (ISO 105-X12) | | |
| SLK | colour fastness to dry ironing (ISO 105-X11) | | |
| SLM | colour fastness to wet ironing (ISO 105-X11) | | |
| SLW | colour fastness to water (ISO 105-E01) | | |
| SLX | colour fastness to Xenolight | | |
| SLZ | colour fastness to rubbing org. Solv. (ISO 105-D02) | | |
| STA | dimensional stability to steaming press - length (DIN 53894-2) | | |
| STB | dimensional stability to steaming press - width (DIN 53894-2) | | |
| STC | dimensional stability to washing - length (ISO 5077+6330) | | |
| STD | dimensional stability to washing - width (ISO 5077+6330) | | |
| STE | dimensional stability to dry cleaning - length (ISO 3175) | | |

| | | | |
|-----|--|--|--|
| STF | dimensional stability to dry cleaning - width (ISO 3175) | | |
|-----|--|--|--|

T16 - dyestuff type

dye stuff used in the fabric dye process

Agency name: eBIZ

tabella cod.: T16

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T16.xml

| Code | Description | Adoption note | Date of insertion |
|------|------------------------|---------------|-------------------|
| AC | chrome acid dyestuff | | |
| AN | acid dyestuff | | |
| CA | basic dyestuff | | |
| DI | direct dyestuff | | |
| DS | disperse dyestuff | | |
| NP | naphtol dyestuff | | |
| PI | pigment | | 01/07/2013 |
| PM | premetallized dyestuff | | |
| RE | reactive dyestuff | | |
| SU | sulfur | | 01/07/2013 |

T19 - fibre type

type of fibre used in a textile product

Agency name: eBIZ

tabella cod.: T19

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T19.xml

| Code | Description | Adoption note | Date of insertion |
|------|----------------|---------------|-------------------|
| AB | abaca | | 20/08/2018 |
| AC | acetate | | |
| AF | other fibres | | |
| AG | alginic fibre | | |
| AL | alfa | | 20/08/2018 |
| CA | hemp | | |
| CC | coir (coconut) | | 20/08/2018 |

| | | | |
|----|--------------------|--|------------|
| CL | chlorofibre | | |
| CO | cotton | | |
| CU | cuprous | | |
| EA | elastan | | |
| EL | Elastodiene | | 20/08/2018 |
| FL | fluorofibre | | |
| GI | broom | | 20/08/2018 |
| GL | textile glass | | |
| HA | hair | | 20/08/2018 |
| HE | henequen | | 20/08/2018 |
| HL | mixed linen | | |
| HL | cotton linen union | | 20/08/2018 |
| JU | jute | | |
| KE | kenaf | | 20/08/2018 |
| KP | kapoc | | 20/08/2018 |
| LI | linen | | |
| LY | lyocell | | 20/08/2018 |
| MA | modacrylic | | |
| MD | modal | | |
| ME | metallized | | |
| MG | maguey | | 20/08/2018 |
| PA | polyamide | | |
| PB | polyureic | | |
| PC | acrylic | | |
| PE | polyethylene | | |
| PI | paper | | 20/08/2018 |
| PL | polyester | | |
| PM | polyimide | | |
| PP | polypropylene | | |
| PR | proteic | | |
| PU | polyurethane | | |
| RA | mamie | | 20/08/2018 |
| SE | silk | | |
| SI | sisal | | 20/08/2018 |
| SN | sun | | 20/08/2018 |

| | | | |
|----|---|--|------------|
| TA | triacetate | | |
| TR | textile residues or unspecified composition | | 20/08/2018 |
| TV | trivinyll | | |
| VI | viscose | | |
| VY | vinylal | | |
| WA | angora | | |
| WB | beaver | | 20/08/2018 |
| WC | cashgora | | |
| WG | vicuna | | |
| WK | camel | | |
| WL | llama | | |
| WM | mohair | | |
| WN | lapin | | 20/08/2018 |
| WO | wool | | |
| WP | alpaca | | |
| WS | cashmere | | |
| WT | Oteer | | 20/08/2018 |
| WU | guanaco | | |
| WV | virgin wool | | |
| WY | yack | | |

T2 - Modes of payment

way or means of payment

Agency name: eBIZ

tabella cod.: T2

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T2.xml

| Code | Description | Adoption note | Date of insertion |
|------|------------------------------|---------------|-------------------|
| BB | bank transfer | | |
| IA | collection through Agent | | |
| IS | collection through Forwarder | | |
| RB | bank receipt | | |
| RD | remittance | | |
| SW | bank SWIFT | | |
| TR | bank draft | | |

T21 - type of document

type or class to which the referenced document belongs

Agency name: eBIZ

tabella cod.: T21

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T21.xml

| Code | Description | Adoption note | Date of insertion |
|-------------|------------------------------------|----------------------|--------------------------|
| BOR | blanket order | | 01/02/2018 |
| CAT | Price catalogue - tech sheet | | |
| CEO | Certificate of origin | | 13/04/2018 |
| CER | Certificate | | 13/04/2018 |
| COC | colour card | | |
| CRN | Credit note | | 08/09/2017 |
| CTO | Checking order | | 01/07/2013 |
| CTR | Contract | | |
| CXF | CxF3 file | | 01/07/2013 |
| DAD | Darn order | | |
| DDT | ddt | | |
| DEA | Despatch advise | | |
| DER | Despatch request | | |
| DR | Document Request | | 02/12/2014 |
| FOR | Forecast | | 02/12/2014 |
| GSO | Garment stock offer | | |
| GSX | Garment stock offer change | | |
| INV | Invoice | | |
| KCC | Knitting-Clothing Commission Order | | 02/12/2014 |
| KCI | Garment in Work Inventory Report | | 02/12/2014 |
| M2M | Made to Measure Production Order | | 02/12/2014 |
| MAS | Master marker | | |
| MCI | Visual merchandising instruction | | 13/04/2018 |
| OCH | Order change | | |
| OFF | Offer | | |
| ORD | Purchase order | | |
| ORP | Order response | | |

| | | | |
|-----|---|--|------------|
| OSR | order status request | | |
| OSS | Offer status | | 02/12/2014 |
| OST | Order status | | |
| OUR | our reference | | |
| QR | Quality Report | | 02/12/2014 |
| RAI | Raw Material in Work Inventory Report | | 02/12/2014 |
| RDC | Raw dyeing commission order | | |
| RDH | Raw dyeing order change | | |
| RDR | Raw dyeing order response | | |
| REA | Receiving advise | | |
| REQ | Request for Offer | | |
| RET | Return | | 02/12/2014 |
| RSC | Spinning commission order | | |
| RSH | Spinning order change | | |
| RSR | Spinning order response | | |
| SCL | process sheet | | |
| TFC | Textile dyeing-finishing commission order | | |
| TFX | Textile Dyeing-Finishing Order Change | | 02/12/2014 |
| TPC | Textile printing commission order | | |
| TPX | Textile Printing Order Change | | 02/12/2014 |
| TWI | Textile in work inventory | | |
| VMI | visual merchandising instructions | | 01/02/2018 |
| WAC | Warping commission order | | |
| WEC | Weaving commission order | | |
| YDC | Yarn dyeing commission order | | |
| YDH | Yarn dyeing order change | | |
| YDR | Yarn dyeing order response | | |
| YTC | Twisting commission order | | |
| YWI | Yarn in work inventory | | |

T264 - fabric printing technology

operation technology used for fabric printing

Agency name: eBIZ

tabella cod.: T264

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T264.xml

| Code | Description | Adoption note | Date of insertion |
|------|------------------------|---------------|-------------------|
| BL | block printing | | |
| DE | devoré printing | | |
| DI | discharge printing | | |
| FC | flock printing | | |
| FL | flat printing | | |
| HA | hand printing | | |
| IJ | inkjet printing | | 01/07/2013 |
| RE | resist printing | | |
| RO | roller printing | | |
| RS | rotary screen printing | | |
| SC | screen printing | | |
| TR | transfer printing | | |

T3 - terms of delivery

specification of the terms of trade (INCOTERMS)

Agency name: Incoterms

tabella cod.: T3

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T3.xml

| Code | Description | Adoption note | Date of insertion |
|------|--|---|-------------------|
| CFR | COST AND FREIGHT (named port of destination) | | |
| CIF | COST, INSURANCE AND FREIGHT (named port of destination) | | |
| CIP | CARRIAGE AND INSURANCE PAID (named place of destination) | | |
| CPA | CARRIAGE PAID (named place of destination) | | |
| DAF | DELIVERED AT FRONTIER (named place) | according to Incoterms® 2010 it is obsolete | 08/12/2017 |
| DAP | Delivered at Place of destination (named place of destination) | according to Incoterms® 2010 | 08/12/2017 |
| DAT | Delivered at Terminal (named place of destination) | according to Incoterms® 2010 | 08/12/2017 |

| | | | |
|---------|--|--|------------|
| DD P | DELIVERED DUTY PAID (named place of destination) | | |
| DD U | DELIVERED DUTY UNPAID (named place of destination) | according to Incoterms® 2010 it is obsolete, use DAP | 08/12/2017 |
| DE Q | DELIVERED EX-QUAY (named port of destination) | according to Incoterms® 2010 it is obsolete | 08/12/2017 |
| DE S | DELIVERED EX-SHIP (named port of destination) | according to Incoterms® 2010 it is obsolete | 08/12/2017 |
| EX W | EX WORKS (named place) | | |
| FA S | FREE ALONGSIDE SHIP (named port of shipment) | | |
| FC A | FREE CARRIER (named place) | | |
| FO B | FREE ON BOARD (named port of shipment) | | |

T38 - transport conditions

special condition of transport or special service requested to the Forwarder

tabella cod.: T38

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T38.xml

| Code | Description | Adoption note | Date of insertion |
|------|--|---------------|-------------------|
| ACC | arrange customs clearance | | |
| CAL | Carrier loads | | |
| CAU | Carrier unloads | | |
| CMR | CMR carnet | | |
| FFN | freight forwarders national conditions | | |
| FLD | special agreement for full loading | | |
| NCC | do not arrange customs clearance | | |
| PPB | packaging paid by Buyer | | |
| PPS | packaging paid by Supplier | | |
| PRO | proof of delivery | | |
| RFR | return container free | | |
| RPC | return container paid by Customer | | |
| RPS | return container paid by Supplier | | |
| SHL | Shipper loads | | |
| SHU | Consignee unloads | | |

T4 - fabric piece inner packing (wrapping) 1

code specifying the type of inner wrapping/packing used for the fabric piece

Agency name: eBIZ

tabella cod.: T4

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T4.xml

| Code | Description | Adoption note | Date of insertion |
|------|------------------------------------|---------------|-------------------|
| A | Folded, whole width | | |
| B | Folded, doubled | | |
| C | Folded, tube products | | |
| D | Spoiled, whole width | | |
| E | Spoiled, doubled, pli: left | | |
| F | Spoiled, doubled, pli: right | | |
| G | Rolled, whole width, single item | | |
| H | Rolled, whole width, several items | | |
| I | Rolled, doubled | | |
| J | Rolled, tube products | | |

T40 - type of transport means

means of transport, in general or referred to a specific leg

Agency name: eBIZ

tabella cod.: T40

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T40.xml

| Code | Description | Adoption note | Date of insertion |
|------|-------------|---------------|-------------------|
| AIR | aircraft | | |
| SHP | ship | | |
| TRU | truck | | |
| VAN | van | | |

T41 - type of Allowance or Charge

coded specification of an Allowance or Charge (elaborated from UNECE 4465)

Agency name: eBIZ

tabella cod.: T41

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T41.xml

| Code | Description | Adoption note | Date of insertion |
|-------------|-----------------------------|----------------------|--------------------------|
| 1 | Agreed settlement | | 19/08/2018 |
| 10 | Costs for draft | | 19/08/2018 |
| 11 | Bank charges | DEPRECATED, use C BK | 19/08/2018 |
| 12 | Agent commission | | 19/08/2018 |
| 14 | Wrong delivery | | 19/08/2018 |
| 15 | Goods returned to agent | | 19/08/2018 |
| 16 | Goods partly returned | | 19/08/2018 |
| 17 | Transport damage | | 19/08/2018 |
| 19 | Trade discount | | 19/08/2018 |
| 2 | Below specification goods | | 19/08/2018 |
| 20 | Deduction for late delivery | DEPRECATED, use C WB | 19/08/2018 |
| 21 | Advertising costs | | 19/08/2018 |
| 22 | Customs duties | | 19/08/2018 |
| 23 | Telephone and postal costs | | 19/08/2018 |
| 24 | Repair costs | | 19/08/2018 |
| 25 | Attorney fees | | 19/08/2018 |
| 26 | Taxes | | 19/08/2018 |
| 3 | Damaged goods | | 19/08/2018 |
| 30 | Direct payment to seller | | 19/08/2018 |

| | | | |
|----|----------------------------------|--|------------|
| 32 | Goods not delivered | | 19/08/2018 |
| 33 | Late delivery | | 19/08/2018 |
| 35 | Goods returned | | 19/08/2018 |
| 36 | Invoice not received | | 19/08/2018 |
| 37 | Credit note to debtor/not to us | | 19/08/2018 |
| 38 | Deducted bonus | | 19/08/2018 |
| 39 | Deducted discount | | 19/08/2018 |
| 4 | Short delivery | | 19/08/2018 |
| 40 | Deducted freight costs | | 19/08/2018 |
| 41 | Deduction against other invoices | | 19/08/2018 |
| 42 | Credit balance(s) | | 19/08/2018 |
| 45 | Debit note to seller | | 19/08/2018 |
| 46 | Discount beyond terms | | 19/08/2018 |
| 48 | Allowance/charge error | | 19/08/2018 |
| 49 | Substitute product | | 19/08/2018 |
| 50 | Terms of sale error | | 19/08/2018 |
| 52 | Wrong invoice | | 19/08/2018 |
| 53 | Duplicate invoice | | 19/08/2018 |
| 54 | Weight error | | 19/08/2018 |
| 55 | Additional charge not authorized | | 19/08/2018 |
| 56 | Incorrect discount | | 19/08/2018 |
| 57 | Price change | | 19/08/2018 |

| | | | |
|---------|--|--|------------|
| 58 | Variation | | 19/08/2018 |
| 59 | Chargeback | | 19/08/2018 |
| 65 | Settlement to agent | | 19/08/2018 |
| 66 | Cash discount | | 19/08/2018 |
| 7 | Payment on account | | 19/08/2018 |
| 70 | Wrong monetary amount resulting from incorrect free goods quantity | | 19/08/2018 |
| 72 | Temporary special promotion | | 19/08/2018 |
| 73 | Difference in tax rate | | 19/08/2018 |
| 74 | Quantity discount | | 19/08/2018 |
| 75 | Promotion discount | | 19/08/2018 |
| 76 | Cancellation deadline passed | | 19/08/2018 |
| 77 | Pricing discount | | 19/08/2018 |
| 78 | Volume discount | | 19/08/2018 |
| 79 | Sundry discount | | 19/08/2018 |
| 8 | Returnable container charge included | | 19/08/2018 |
| 9 | Invoice error | | 19/08/2018 |
| AW A | bonus for works ahead of schedule | | |
| CBK | bank charges | | |
| CCR | servizio di corriere | | |
| CIN | insurance | | |
| CLB | labelling | | |
| CPK | packing | | |
| CSP | special packing | | |
| CW B | penalty for works behind schedule | | |

T44 - additional code type

qualifier of the additional coding of a product

Agency name: eBIZ

tabella cod.: T44

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T44.xml

| Code | Description | Adoption note | Date of insertion |
|------|-----------------------------|---------------|-------------------|
| CC | colour card | | |
| CL | sales collection | | |
| CO | company identification code | | 08/09/2017 |
| DY | dye number | | |
| LT | lot number | | |
| MDI | Made in | | 08/09/2017 |
| MS | manufacturing state | | |
| PKG | packaging | | 09/09/2014 |
| PL | product line | | |
| RGB | RGB value | | |
| SE | selvedge code | | |

T45 - fabric print parameter type

code specifying a characteristic or parameter of the fabric printing

Agency name: eBIZ

tabella cod.: T45

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T45.xml

| Code | Description | Adoption note | Date of insertion |
|------|-------------------|---------------|-------------------|
| NC | number of colours | | |
| RL | repeat length | | |
| RW | repeat width | | |

T5 - fabric piece inner packing (wrapping) 2

code specifying the sub-type of inner wrapping/packing used for the fabric piece

Agency name: eBIZ

tabella cod.: T5

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T5.xml

| Code | Description | Adoption note | Date of insertion |
|------|---|---------------|-------------------|
| A | Open | | |
| B | Folded once, not looped | | |
| C | Folded twice, not looped | | |
| H | Folded once, looped | | |
| I | Folded twice, looped | | |
| J | Without inner object, right side inside | | |
| K | On carton or spooling plank, right side inside | | |
| L | On spool (for pressure sensitive products), right side inside | | |
| M | Without inner object, left side inside | | |
| N | On carton or spooling plank, left side inside | | |
| O | On spool (for pressure sensitive products), left side inside | | |
| P | Without inner object, right side inside (deprecated code) | | |
| Q | On carton, right side inside | | |
| R | On wooden stick, right side inside | | |
| S | Without inner object, left side inside (deprecated code) | | |
| T | On carton, left side inside | | |
| U | On wooden stick, left side inside | | |

T52 - fabric piece status

code used to describe the status of a fabric piece with reference to the control

Agency name: eBIZ

tabella cod.: T52

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T52.xml

| Code | Description | Adoption note | Date of insertion |
|------|--------------------------|---------------|-------------------|
| 0 | first registration | | |
| C | registration from return | | |
| F | stopped | | |
| H | handling | | |
| R | returned | | |
| S | held | | |

| | | | |
|---|-------------|--|--|
| T | deliverable | | |
|---|-------------|--|--|

T6 - fabric piece outer packing

code specifying the type of outer wrapping or packing used for the fabric piece

Agency name: eBIZ

tabella cod.: T6

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T6.xml

| Code | Description | Adoption note | Date of insertion |
|------|--|---------------|-------------------|
| 0 | Not wrapped | | |
| 1 | Totally wrapped | | |
| 2 | Wrapped, one side open | | |
| 3 | Wrapped, both sides open | | |
| 4 | Wrapped, one side open, with show corner | | |
| 5 | Wrapped in cartons | | |
| 6 | Double wrapped | | |

T61 - duty or tax or fee type

duty or tax or fee type

Agency name: eBIZ

tabella cod.: T61

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T61.xml

| Code | Description | Adoption note | Date of insertion |
|------|-------------------|---------------|-------------------|
| BOL | stamp duty | | 01/07/2013 |
| CUD | customs duty | | 01/07/2013 |
| ENV | environmental tax | | 01/07/2013 |
| FRE | no tax | | 01/07/2013 |
| OTH | other tax charges | | 01/07/2013 |
| VAT | value added tax | | 01/07/2013 |

T62 - duty or tax or fee category

duty or tax or fee category

Agency name: eBIZ

tabella cod.: T62

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T62.xml

| Code | Description | Adoption note | Date of insertion |
|------|---------------------------|---------------|-------------------|
| AA | lower than standard rate | | 01/07/2013 |
| E | tax not applicable | | 01/07/2013 |
| H | higher than standard rate | | 01/07/2013 |
| O | outside scope of tax | | 01/07/2013 |
| S | standard rate | | 01/07/2013 |
| Z | zero rate goods | | 01/07/2013 |

T8 - Modes of Transport

way of transport, in general or referred to the specified leg

Agency name: eBIZ

tabella cod.: T8

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T8.xml

| Code | Description | Adoption note | Date of insertion |
|------|------------------------|---------------|-------------------|
| 1 | MARITIME TRANSPORT | | |
| 10 | Courier | | 01/07/2013 |
| 2 | RAIL TRANSPORT | | |
| 3 | ROAD TRANSPORT | | |
| 4 | AIR TRANSPORT | | |
| 5 | MAIL | | |
| 6 | AIR + SHIP TRANSPORT | | |
| 8 | INLAND WATER TRANSPORT | | |
| 9 | MODE UNKNOWN | | |

T9 - ISO4217 - Currency

currency code

Agency name: ISO

tabella cod.: T9

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T9.xml

Table not printed: there are 205 elements, more than the maximum specified for printing: 99.