



<http://www.ebiz-tcf.eu>

DRAFT

IMPLEMENTATION GUIDE

TRANSACTION "GENERAL PURPOSE REQUEST"

Version: draft

Date of release: 17/5/2019

Document code: G039

technical Documentation: <http://www.ebiz.enea.it>

XML Schemas repository: <http://www.ebiz.enea.it/moda-ml/repository/schema/draft/default.asp>

Guides repository: <http://www.ebiz.enea.it/moda-ml/repository/guide/draft/default.asp>

Guide filename: G039-eBIZ-GeneralPurposeRequest.pdf

0. PREMISE

This document contains a proposal for the updating and extension of eBIZ specifications starting from the eBIZ version released as CEN CWA 16667 in 2013. Under the name of 'Draft version' it is reported the result of an extensive work of analysis and consultation aimed at developing and maintaining eBIZ specifications.

In particular, the content of this proposal is the result of various activities, mainly those carried out within the framework of the **eBIZ 4.0 project** funded by the European Commission, call COS-DESIGN-2015-3-06, topic COS-2015-DESIGN-2.

The technical contents are backwards compatible with the latest official published version.

1. BUSINESS DESCRIPTION

1.1 Scope

This document is used to solicit the sending of a document when this is produced only on request (e.g.: the Order Status)


1.2 Generalities

The message is issued to request a particular (paper or electronic) business document.

With this document it is possible to indicate the type of the requested document , and one or more blocks of filtering criteria (the Party, identified by legal name or id, to which it refers, and/or one or more items to be referred to, eg season, article or fabric or component code, . . .)

1.3. Possible scenario

Knitting and assembling



1.4. Best practices

The document could be used to request the order progress status for a season and a group of articles whose code is indicated; in another case it could be sent to a warehouse manager to request the inventory related to one or more particular brands whose legal name is indicated; another example is the use for requesting the PartyIn document concerning information on one or more parties, indicating their legal names or unique codes.

2. IMPLEMENTATION GUIDE

2.1 General structure of XML document

All the business data that can be exchanged through this class of documents are shown in the following "document structure", that provides a simplified vision of the Schema.

In particular:

- the two numbers following each element define its "cardinality" (minimum and maximum number of occurrences); the minimum equal zero indicates that the element is optional, the minimum greater than zero indicates that is mandatory;
- the bold character denotes the complex elements (aggregates of simple elements) that were built for the sake of functionality and re-usability of some complex informations sets. The child elements in each parent element are easily spotted as "indented";
- the symbol "@" denotes an attribute of the preceding element; here "the usage indicator (optional, required, ...)" is shown in square brackets.

Structure

GPDocRequest

@version [Optional] [Default= draft]

@useProfile [Optional]

| msgN 1-1

| msgDate 1-1

| *@dateForm [Optional]*

| **refDoc 0-9**

| *@docType [Required]*

| | docID 1-2

| | *@numberingOrg [Optional]*

| | docDate 0-1

| | *@dateForm [Optional]*

| | season 0-1

| | *@numberingOrg [Optional]*

| | *@codeList [Optional]*

| | *@listName [Optional]*

| | *@listVersion [Optional]*

| | itemID 0-1

| **attachment 0-1**

| | *@uid [Optional]*

| | | fileName 0-1

| | | *@numberingOrg [Optional]*

| | | binaryObject 0-1

| | | *@format [Optional]*

| | | *@mime [Optional]*

| | | *@encoding [Optional]*

| | | *@characterSet [Optional]*

| | **externalReference 0-99**

| | | uri 1-1

| | | *@isURL [Optional] [Default= true]*

| | | mimeTypeCode 0-1

| | | formatCode 0-1

| | | encodingCode 0-1

| | | characterSetCode 0-1

| **buyer 1-1**

| | *@logo [Optional]*

| | *@sender [Optional]*

| | id 1-1

- | | *@numberingOrg [Optional]*
- | | additionalIdentifier 0-9
- | | *@numberingOrg [Optional]*
- | | *@idQualifier [Optional]*
- | | legalName 0-1
- | | dept 0-1
- | | subDept 0-1
- | | person 0-1
- | | *@email [Optional]*
- | | *@phone [Optional]*
- | | *@fax [Optional]*
- | | street 0-1
- | | city 0-1
- | | subCountry 0-1
- | | country 0-1
- | | postCode 0-1

| **supplier 1-1**

- | | *@logo [Optional]*
- | | *@sender [Optional]*
- | | id 1-1
- | | *@numberingOrg [Optional]*
- | | additionalIdentifier 0-9
- | | *@numberingOrg [Optional]*
- | | *@idQualifier [Optional]*
- | | legalName 0-1
- | | dept 0-1
- | | subDept 0-1
- | | person 0-1
- | | *@email [Optional]*
- | | *@phone [Optional]*
- | | *@fax [Optional]*
- | | street 0-1
- | | city 0-1
- | | subCountry 0-1
- | | country 0-1
- | | postCode 0-1

| requestDocType 1-1

| **itemRestrict 0-99**

- | | id 0-1
- | | *@numberingOrg [Optional]*
- | | legalName 0-1
- | | season 0-1
- | | *@numberingOrg [Optional]*
- | | *@codeList [Optional]*
- | | *@listName [Optional]*
- | | *@listVersion [Optional]*

- choose -

| **garmentPartCode 0-2**

- | | *@numberingOrg [Optional]*
- | | gPart 1-1
- | | mod 1-1
- | | *@numberingOrg [Optional]*
- | | *@codeList [Optional]*
- | | *@listName [Optional]*
- | | *@listVersion [Optional]*
- | | fabric 0-1
- | | *@numberingOrg [Optional]*
- | | *@codeList [Optional]*

| | @listName [Optional]
| | @listVersion [Optional]
| | color 0-1
| | @numberingOrg [Optional]
| | @codeList [Optional]
| | @listName [Optional]
| | @listVersion [Optional]
| | added 0-19
| | @numberingOrg [Optional]
| | @addType [Optional]
| | size 0-1
| | @codeList [Optional]
| | description 0-unbounded
| | @ln [Optional]

- or -

| | **acsCode 0-2**

| | @numberingOrg [Optional]
| | art 1-1
| | @numberingOrg [Optional]
| | @codeList [Optional]
| | @listName [Optional]
| | @listVersion [Optional]
| | pattern 0-1
| | @numberingOrg [Optional]
| | @codeList [Optional]
| | @listName [Optional]
| | @listVersion [Optional]
| | color 0-1
| | @numberingOrg [Optional]
| | @codeList [Optional]
| | @listName [Optional]
| | @listVersion [Optional]
| | added 0-9
| | @numberingOrg [Optional]
| | @addType [Optional]
| | description 0-unbounded
| | @ln [Optional]

- or -

| | **garmentCode 0-2**

| | @numberingOrg [Optional]

- choose -

| | **garmentCodeB 1-1**

| | @numberingOrg [Optional]
| | mod 1-1
| | @numberingOrg [Optional]
| | @codeList [Optional]
| | @listName [Optional]
| | @listVersion [Optional]
| | fabric 0-1
| | @numberingOrg [Optional]
| | @codeList [Optional]
| | @listName [Optional]
| | @listVersion [Optional]
| | color 0-1
| | @numberingOrg [Optional]
| | @codeList [Optional]
| | @listName [Optional]
| | @listVersion [Optional]

| | **garmentVariant 0-9**

| | variantType 1-1
| | @numberingOrg [Optional]

```

| | | | @codeList [Optional]
| | | | @listName [Optional]
| | | | @listVersion [Optional]
| | | | variantCode 1-1
| | | | @numberingOrg [Optional]
| | | | @codeList [Optional]
| | | | @listName [Optional]
| | | | @listVersion [Optional]
| | | | drop 0-1
| | | | @codeList [Optional]
| | | | size 0-1
| | | | @codeList [Optional]
| | | | artGroup 0-1
| | | | @numberingOrg [Optional]
| | | | @codeList [Optional]
| | | | @listName [Optional]
| | | | @listVersion [Optional]
| | | | added 0-9
| | | | @numberingOrg [Optional]
| | | | @addType [Optional]
| | | | description 0-unbounded
| | | | @ln [Optional]

```

- or -

```

| | | | garmentCodeA 1-1
| | | | art 1-1
| | | | @numberingOrg [Optional]
| | | | @codeList [Optional]
| | | | @listName [Optional]
| | | | @listVersion [Optional]
| | | | description 0-unbounded
| | | | @ln [Optional]

```

- end choose -

- or -

```

| | | | texCode 0-2
| | | | @numberingOrg [Optional]
| | | | art 1-1
| | | | @numberingOrg [Optional]
| | | | @codeList [Optional]
| | | | @listName [Optional]
| | | | @listVersion [Optional]
| | | | pattern 0-1
| | | | @numberingOrg [Optional]
| | | | @codeList [Optional]
| | | | @listName [Optional]
| | | | @listVersion [Optional]
| | | | color 0-1
| | | | @numberingOrg [Optional]
| | | | @codeList [Optional]
| | | | @listName [Optional]
| | | | @listVersion [Optional]
| | | | added 0-9
| | | | @numberingOrg [Optional]
| | | | @addType [Optional]
| | | | description 0-unbounded
| | | | @ln [Optional]

```

- or -

```

| | | | yarnCode 0-2
| | | | @numberingOrg [Optional] [Default= CL]
| | | | art 1-1
| | | | @numberingOrg [Optional]
| | | | @codeList [Optional]

```

```

| | | @listName [Optional]
| | | @listVersion [Optional]
| | | color 0-1
| | | @numberingOrg [Optional]
| | | @codeList [Optional]
| | | @listName [Optional]
| | | @listVersion [Optional]
| | | added 0-9
| | | @numberingOrg [Optional]
| | | @addType [Optional]
| | | description 0-unbounded
| | | @ln [Optional]
- end choose -
| | note 0-99
| | @numberingOrg [Optional]
| | @codeList [Optional]
| | @noteLabel [Optional]

```

timeRestrict 0-1

```

| | validityStart 0-1
| | @dateForm [Optional]
| | validityEnd 0-1
| | @dateForm [Optional]

```

```

| note 0-99
| @numberingOrg [Optional]
| @codeList [Optional]
| @noteLabel [Optional]

```

2.2 Detailed description of document elements

Following tables show all elements (complex and simple) used in this document. Description includes: 1) element's information: xml tag, name, brief description, data type and syntax constraints; 2) information about use of the element in a particular position in the document: xpath and possible associated notes.

2.2.1 Complex elements (Aggregate Business Information Entities)

Complex elements are those elements whose content is composed of other elements (childs). Complex elements are alphabetically ordered.

| | |
|--------------------------|---|
| acsCode | full codification identifying an accessory product usually coupled with garment or other fashion product (XPath GPDocRequest/itemRestrict/acsCode) 0-2 |
| attachment | an attached document. An attachment can refer to an external document or be included with the document being exchanged (XPath GPDocRequest/refDoc/attachment) 0-1 |
| buyer | details of the Buyer (party that buys the good or service that is object of the current collaborative process) - base type: Nad, (XPath GPDocRequest/buyer) 1-1 |
| externalReference | details about an external object, such as a document stored at a remote location (XPath GPDocRequest/refDoc/attachment/externalReference) 0-99 |
| garmentCode | codification of the garment product (XPath GPDocRequest/itemRestrict/garmentCode) 0-2 |
| garmentCodeA | codification of the garment product- type A (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeA) 1-1 - note: <i>here the barcode EAN-13 or EAN-8 should be specified</i> |
| garmentCodeB | codification of the garment product - type B (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB) 1-1 |
| garmentPartCode | codification of the component or part of a fashion article (XPath GPDocRequest/itemRestrict/garmentPartCode) 0-2 |
| garmentVariant | garment product variant (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/garmentVariant) 0-9 |
| itemRestrict | Item restriction to be applied on the document requested, expressed as an article code or a Party code (XPath GPDocRequest/itemRestrict) 0-99 - note: <i>in case of use of this item restriction at least one of the child elements must be present</i> |
| refDoc | identification of a document and of an item thereof, to which the message makes reference (XPath GPDocRequest/refDoc) 0-9 |
| supplier | details of the Supplier (party that supplies the good or service that is object of the current collaborative process) - base type: Nad, (XPath GPDocRequest/supplier) 1-1 |
| texCode | full codification of the textile product (XPath GPDocRequest/itemRestrict/texCode) 0-2 |

| | |
|---------------------|--|
| timeRestrict | time restriction to be applied on the document requested, expressed as a period of validity/application of the document requested (XPath GPDocRequest/timeRestrict) 0-1 |
| yarnCode | full codification of a yarn product (XPath GPDocRequest/itemRestrict/yarnCode) 0-2 |

2.2.2 Simple elements (Basic Business Information Entities)

Simple elements are those elements whose content is characterized by a data type plus a domain of possible values. Simple elements are alphabetically ordered.

| | |
|-----------------------------|--|
| added | additional code of the product (complementing the formers) - base type: string, max length: 80, (XPath GPDocRequest/itemRestrict/texCode/added) 0-9 - note: <i>here an additional codification (see table T44) can be specified</i> (XPath GPDocRequest/itemRestrict/garmentPartCode/added) 0-19 (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/added) 0-9 (XPath GPDocRequest/itemRestrict/acsCode/added) 0-9 - note: <i>here an additional codification (see table T44) can be specified</i> (XPath GPDocRequest/itemRestrict/yarnCode/added) 0-9 - note: <i>here an additional codification (see table T44) can be specified</i> |
| additionalIdentifier | additional identification code of a Party, for example customs registries or others - base type: string, max length: 15, (XPath GPDocRequest/buyer/additionalIdentifier) 0-9 - note: <i>identifiers for example for exports, such as MID (Manufacturer Identification Code), EORI (E.O.R.I. - Economic Operator Registration and Identification)</i> (XPath GPDocRequest/supplier/additionalIdentifier) 0-9 - note: <i>identifiers for example for exports, such as MID (Manufacturer Identification Code), EORI (E.O.R.I. - Economic Operator Registration and Identification)</i> |
| @addType | qualifier of the additional coding of a product - base type: string, cod. table: T44 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T44.xml (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/added/@addType) [Optional] - nota: <i>addType allows the clarification of the meaning of the added element content; it is strongly suggested to use it always.</i> (XPath GPDocRequest/itemRestrict/acsCode/added/@addType) [Optional] - nota: <i>addType allows the clarification of the meaning of the added element content; it is strongly suggested to use it always.</i> (XPath GPDocRequest/itemRestrict/yarnCode/added/@addType) [Optional] - nota: <i>addType allows the clarification of the meaning of the added element content; it is strongly suggested to use it always.</i> (XPath GPDocRequest/itemRestrict/texCode/added/@addType) [Optional] - nota: <i>addType allows the clarification of the meaning of the added element content; it is strongly suggested to use it always.</i> (XPath GPDocRequest/itemRestrict/garmentPartCode/added/@addType) [Optional] - nota: <i>addType allows the clarification of the meaning of the added element content; it is strongly suggested to use it always.</i> |
| art | article number of the product - base type: string, max length: 80, (XPath GPDocRequest/itemRestrict/texCode/art) 1-1 - note: <i>can be used either for the base-article (excluding pattern/colour) or for the SKU</i> (XPath GPDocRequest/itemRestrict/yarnCode/art) 1-1 (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeA/art) 1-1 |

| | |
|------------------|--|
| | (XPath GPDocRequest/itemRestrict/acsCode/art) 1-1 |
| artGroup | code identifying a class of products - base type: string, max length: 40, (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/artGroup) 0-1 |
| binaryObject | a binary large object containing an attached document - base type: base64Binary, (XPath GPDocRequest/refDoc/attachment/binaryObject) 0-1 |
| @characterSet | the character set of the binary object if the mime type is text - base type: normalizedString, (XPath GPDocRequest/refDoc/attachment/binaryObject/@characterSet) [Optional] |
| characterSetCode | the character set of an external document - base type: normalizedString, (XPath GPDocRequest/refDoc/attachment/externalReference/characterSetCode) 0-1 |
| city | name of the city (town, village) - base type: string, max length: 40, (XPath GPDocRequest/supplier/city) 0-1 (XPath GPDocRequest/buyer/city) 0-1 |
| @codeList | it specifies the URL where the list of codes used to make an instance of the element can be found - base type: string, max length: 255, (XPath GPDocRequest/itemRestrict/garmentPartCode/mod/@codeList) [Optional] - nota: <i>this attribute should be ALTERNATIVE to the others</i> (XPath GPDocRequest/itemRestrict/acsCode/pattern/@codeList) [Optional] - nota: <i>this attribute should be ALTERNATIVE to the others</i> (XPath GPDocRequest/itemRestrict/season/@codeList) [Optional] (XPath GPDocRequest/itemRestrict/garmentPartCode/color/@codeList) [Optional] - nota: <i>this attribute could be used as alternative to the others</i> (XPath GPDocRequest/itemRestrict/garmentPartCode/size/@codeList) [Optional] (XPath GPDocRequest/itemRestrict/garmentPartCode/fabric/@codeList) [Optional] - nota: <i>this attribute should be ALTERNATIVE to the others</i> (XPath GPDocRequest/itemRestrict/acsCode/art/@codeList) [Optional] - nota: <i>this attribute should be ALTERNATIVE to the others</i> (XPath GPDocRequest/itemRestrict/texCode/pattern/@codeList) [Optional] - nota: <i>this attribute should be ALTERNATIVE to the others</i> (XPath GPDocRequest/itemRestrict/texCode/color/@codeList) [Optional] - nota: <i>this attribute could be used as alternative to the others</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeA/art/@codeList) [Optional] - nota: <i>this attribute should be ALTERNATIVE to the others</i> (XPath GPDocRequest/itemRestrict/texCode/art/@codeList) [Optional] - nota: <i>this attribute should be ALTERNATIVE to the others</i> (XPath GPDocRequest/itemRestrict/note/@codeList) [Optional] - nota: <i>must be used to provide (URL) the list of codes used in "noteLabel"</i> (XPath GPDocRequest/note/@codeList) [Optional] - nota: <i>must be used to provide (URL) the list of codes used in "noteLabel"</i> (XPath GPDocRequest/itemRestrict/yarnCode/art/@codeList) [Optional] - nota: <i>this attribute should be ALTERNATIVE to the others</i> (XPath GPDocRequest/itemRestrict/yarnCode/color/@codeList) [Optional] - nota: <i>this attribute could be used as alternative to the others</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/artGroup/@codeList) [Optional] - nota: <i>this attribute should be ALTERNATIVE to the others</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/fabric/@codeList) [Optional] - nota: <i>this attribute should be ALTERNATIVE to the others</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/color/@codeList) [Optional] - nota: <i>this attribute could be used as alternative to the others</i> (XPath GPDocRequest/itemRestrict/acsCode/color/@codeList) [Optional] |

| | |
|-------------|---|
| | <p>- nota: <i>this attribute could be used as alternative to the others</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/mod/@codeList) [Optional]</p> <p>- nota: <i>this attribute should be ALTERNATIVE to the others</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/drop/@codeList) [Optional]</p> <p>(XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/size/@codeList) [Optional]</p> <p>(XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/garmentVariant/variantType/@codeList) [Optional]</p> <p>- nota: <i>this attribute should be ALTERNATIVE to the others</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/garmentVariant/variantCode/@codeList) [Optional]</p> <p>- nota: <i>this attribute should be ALTERNATIVE to the others</i> (XPath GPDocRequest/refDoc/season/@codeList) [Optional]</p> |
| color | <p>colour number of the product, when not included in the model or fabric code</p> <p>- base type: string, max length: 15, (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/color) 0-1 (XPath GPDocRequest/itemRestrict/yarnCode/color) 0-1 (XPath GPDocRequest/itemRestrict/garmentPartCode/color) 0-1</p> <p>- note: <i>when a garment component, it should be the code assigned to the garment article</i> (XPath GPDocRequest/itemRestrict/texCode/color) 0-1 (XPath GPDocRequest/itemRestrict/acsCode/color) 0-1</p> |
| country | <p>code of the nation</p> <p>- base type: string, cod. table: T10 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T10.xml (XPath GPDocRequest/supplier/country) 0-1 (XPath GPDocRequest/buyer/country) 0-1</p> |
| @dateForm | <p>format used for the date</p> <p>- base type: string, cod. table: NT29 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT29.xml (XPath GPDocRequest/timeRestrict/validityEnd/@dateForm) [Optional] (XPath GPDocRequest/timeRestrict/validityStart/@dateForm) [Optional] (XPath GPDocRequest/msgDate/@dateForm) [Optional] (XPath GPDocRequest/refDoc/docDate/@dateForm) [Optional]</p> |
| dept | <p>name or code of a contact department within a Party</p> <p>- base type: string, max length: 40, (XPath GPDocRequest/supplier/dept) 0-1 (XPath GPDocRequest/buyer/dept) 0-1</p> |
| description | <p>free text description. The content of the element must be unique, it might be translated and repeated into more languages (thus no more than one instance for each language).</p> <p>- base type: string, max length: 250, (XPath GPDocRequest/itemRestrict/texCode/description) 0-unbounded</p> <p>- note: <i>Product description</i> (XPath GPDocRequest/itemRestrict/garmentPartCode/description) 0-unbounded</p> <p>- note: <i>Product part description</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeA/description) 0-unbounded</p> <p>- note: <i>Product description</i> (XPath GPDocRequest/itemRestrict/acsCode/description) 0-unbounded</p> <p>- note: <i>Product description</i> (XPath GPDocRequest/itemRestrict/yarnCode/description) 0-unbounded</p> <p>- note: <i>Product description</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/description) 0-unbounded</p> <p>- note: <i>Product description</i></p> |

| | |
|--------------|--|
| docDate | date of issue of the referenced document, according to one of the patterns YYYY-MM-DD, YYYY-MM-DD:HH-MM or YYYY-WW. - base type: string, (XPath GPDocRequest/refDoc/docDate) 0-1 |
| docID | identification number of the referenced document SINCE 2008-1 ITS USE IN THE HEADER IS DISCOURAGED (REPLACED BY msgID) - base type: string, max length: 80, (XPath GPDocRequest/refDoc/docID) 1-2 |
| @docType | type or class to which the referenced document belongs - base type: string, cod. table: T21 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T21.xml (XPath GPDocRequest/refDoc/@docType) [Required] |
| drop | drop number of the garment - base type: string, max length: 15, (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/drop) 0-1 - note: <i>Fill this element if the drop is the same for all the sizes of the model. Otherway specify it within the csRange element</i> |
| @email | electronic mail address of the contact person within a Party - base type: string, max length: 250, (XPath GPDocRequest/buyer/person/@email) [Optional] (XPath GPDocRequest/supplier/person/@email) [Optional] |
| @encoding | specifies the decoding algorithm of the binary object - base type: normalizedString, (XPath GPDocRequest/refDoc/attachment/binaryObject/@encoding) [Optional] |
| encodingCode | the encoding/decoding algorithm used with the external object - base type: normalizedString, (XPath GPDocRequest/refDoc/attachment/externalReference/encodingCode) 0-1 |
| fabric | fabric number of the garment - base type: string, max length: 15, (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/fabric) 0-1 (XPath GPDocRequest/itemRestrict/garmentPartCode/fabric) 0-1 - note: <i>when a garment component, it should be the code assigned to the garment article</i> |
| @fax | fax number of the contact person within a Party - base type: string, max length: 35, (XPath GPDocRequest/buyer/person/@fax) [Optional] (XPath GPDocRequest/supplier/person/@fax) [Optional] |
| fileName | unique identifier (name) of the file - base type: string, max length: 255, (XPath GPDocRequest/refDoc/attachment/fileName) 0-1 |
| @format | the format of the binary content - base type: string, (XPath GPDocRequest/refDoc/attachment/binaryObject/@format) [Optional] |
| formatCode | the format of the external object - base type: normalizedString, (XPath GPDocRequest/refDoc/attachment/externalReference/formatCode) 0-1 |
| gPart | code specifying the type of component or part of a fashion product (sleeve, neck, ...) - base type: string, cod. table: T48 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T48.xml (XPath GPDocRequest/itemRestrict/garmentPartCode/gPart) 1-1 |
| id | primary identification code of a Party; it is recommended the format: nation code (ISO 3166) + VAT identification number (11 crt), with the qualifier "num |

| | |
|--------------|---|
| | beringOrg"= MF - base type: string, max length: 15, (XPath GPDocRequest/supplier/id) 1-1 (XPath GPDocRequest/buyer/id) 1-1 (XPath GPDocRequest/itemRestrict/id) 0-1 |
| @idQualifier | Qualification of the identifier. - base type: string, (XPath GPDocRequest/buyer/additionalIdentifier/@idQualifier) [Optional] - nota: <i>this attribute should be used when the numberingOrg attribute is not enough to declare the type of identifier</i> (XPath GPDocRequest/supplier/additionalIdentifier/@idQualifier) [Optional] - nota: <i>this attribute should be used when the numberingOrg attribute is not enough to declare the type of identifier</i> |
| @isURL | it indicates if the referred element is an URL (true) or not (false) - base type: boolean, (XPath GPDocRequest/refDoc/attachment/externalReference/uri/@isURL) [Optional] [Default= true] - nota: <i>usage of URLs is recommended</i> |
| itemID | number of the line/item of the referenced document - base type: string, max length: 6, (XPath GPDocRequest/refDoc/itemID) 0-1 |
| legalName | legal name of a Party - base type: string, max length: 250, (XPath GPDocRequest/itemRestrict/legalName) 0-1 (XPath GPDocRequest/supplier/legalName) 0-1 (XPath GPDocRequest/buyer/legalName) 0-1 |
| @listName | the name of the list of codes used to make an instance of the element (it might be thought as descriptive element, i.e. 'fabric printing technologies', or not, i.e. "T264") - base type: string, max length: 40, (XPath GPDocRequest/itemRestrict/acsCode/color/@listName) [Optional] - nota: <i>this attribute should always be used coupled with "numberingOrg"</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/mod/@listName) [Optional] - nota: <i>this attribute should always be used coupled with "numberingOrg"</i> (XPath GPDocRequest/itemRestrict/yarnCode/color/@listName) [Optional] - nota: <i>this attribute should always be used coupled with "numberingOrg"</i> (XPath GPDocRequest/itemRestrict/yarnCode/art/@listName) [Optional] - nota: <i>this attribute should always be used coupled with "numberingOrg"</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/artGroup/@listName) [Optional] - nota: <i>this attribute should always be used coupled with "numberingOrg"</i> (XPath GPDocRequest/itemRestrict/texCode/pattern/@listName) [Optional] - nota: <i>this attribute should always be used coupled with "numberingOrg"</i> (XPath GPDocRequest/itemRestrict/texCode/art/@listName) [Optional] - nota: <i>this attribute should always be used coupled with "numberingOrg"</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeA/art/@listName) [Optional] - nota: <i>this attribute should always be used coupled with "numberingOrg"</i> (XPath GPDocRequest/refDoc/season/@listName) [Optional] (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/color/@listName) [Optional] - nota: <i>this attribute should always be used coupled with "numberingOrg"</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/fabric/@listName) [Optional] - nota: <i>this attribute should always be used coupled with "numberingOrg"</i> (XPath GPDocRequest/itemRestrict/texCode/color/@listName) [Optional] - nota: <i>this attribute should always be used coupled with "numberingOrg"</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/garmentVariant/variantCode/@listName) [Optional] |

| | |
|---------------------|--|
| | <ul style="list-style-type: none"> - nota: <i>this attribute should always be used coupled with “numberingOrg”</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/ garmentVariant/variantType/@listName) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg”</i> (XPath GPDocRequest/itemRestrict/garmentPartCode/fabric/@listName) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg”</i> (XPath GPDocRequest/itemRestrict/acsCode/pattern/@listName) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg”</i> (XPath GPDocRequest/itemRestrict/season/@listName) [Optional] (XPath GPDocRequest/itemRestrict/acsCode/art/@listName) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg”</i> (XPath GPDocRequest/itemRestrict/garmentPartCode/mod/@listName) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg”</i> (XPath GPDocRequest/itemRestrict/garmentPartCode/color/@listName) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg”</i> |
| <p>@listVersion</p> | <p>it specifie the version of the list of codes used to make an instance of the element</p> <ul style="list-style-type: none"> - base type: string, max length: 6, (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/ mod/@listVersion) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/itemRestrict/acsCode/art/@listVersion) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/itemRestrict/garmentPartCode/mod/@listVersion) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/itemRestrict/garmentPartCode/fabric/@listVersion) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/ artGroup/@listVersion) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/ fabric/@listVersion) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeA/ art/@listVersion) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/itemRestrict/garmentPartCode/color/@listVersion) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/ color/@listVersion) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/itemRestrict/acsCode/color/@listVersion) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/itemRestrict/yarnCode/art/@listVersion) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/itemRestrict/acsCode/pattern/@listVersion) [Optional] - nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/ garmentVariant/variantType/@listVersion) [Optional] |

| | |
|----------|---|
| | <p>- nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/itemRestrict/yarnCode/color/@listVersion) [Optional]</p> <p>- nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/garmentVariant/variantCode/@listVersion) [Optional]</p> <p>- nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/itemRestrict/texCode/art/@listVersion) [Optional]</p> <p>- nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/refDoc/season/@listVersion) [Optional] (XPath GPDocRequest/itemRestrict/texCode/pattern/@listVersion) [Optional]</p> <p>- nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/itemRestrict/texCode/color/@listVersion) [Optional]</p> <p>- nota: <i>this attribute should always be used coupled with “numberingOrg” and “listName”</i> (XPath GPDocRequest/itemRestrict/season/@listVersion) [Optional]</p> |
| @ln | <p>Language code. - base type: string, (XPath GPDocRequest/itemRestrict/texCode/description/@ln) [Optional] (XPath GPDocRequest/itemRestrict/yarnCode/description/@ln) [Optional] (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/description/@ln) [Optional] (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeA/description/@ln) [Optional] (XPath GPDocRequest/itemRestrict/acsCode/description/@ln) [Optional] (XPath GPDocRequest/itemRestrict/garmentPartCode/description/@ln) [Optional]</p> |
| @logo | <p>company logo (URL of the image jpeg or gif). It is recommended that the width of the image does not exceed 640 pixel. - base type: string, max length: 255, (XPath GPDocRequest/buyer/@logo) [Optional] (XPath GPDocRequest/supplier/@logo) [Optional]</p> |
| @mime | <p>the mime type of the binary object - base type: normalizedString, (XPath GPDocRequest/refDoc/attachment/binaryObject/@mime) [Optional]</p> |
| mimeCode | <p>mime type of the external object - base type: normalizedString, (XPath GPDocRequest/refDoc/attachment/externalReference/mimeCode) 0-1</p> |
| mod | <p>model number of the garment - base type: string, max length: 15, (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/mod) 1-1 (XPath GPDocRequest/itemRestrict/garmentPartCode/mod) 1-1 - note: <i>when a garment component, it should be the code assigned to the garment article</i></p> |
| msgDate | <p>date of issue of the present message (xml document), according to one of the patterns YYYY-MM-DD, YYYY-MM-DD:HH-MM or YYYY-WW. - base type: string, (XPath GPDocRequest/msgDate) 1-1</p> |
| msgN | <p>identification number given to the message (xml document) by its issuer. In case of more despatches of the same business document, it changes. - base type: string, max length: 35, (XPath GPDocRequest/msgN) 1-1</p> |

| | |
|---------------|--|
| note | <p>free text or structured (computer processing) note. For note structuring use the attributes "noteLabel" and "codelist"</p> <ul style="list-style-type: none"> - base type: string, max length: 350, (XPath GPDocRequest/note) 0-99 (XPath GPDocRequest/itemRestrict/note) 0-99 |
| @noteLabel | <p>subject qualifier of a note</p> <ul style="list-style-type: none"> - base type: string, max length: 35, (XPath GPDocRequest/itemRestrict/note/@noteLabel) [Optional] - nota: <i>must be used to qualify the subject of the note</i> (XPath GPDocRequest/note/@noteLabel) [Optional] - nota: <i>must be used to qualify the subject of the note</i> |
| @numberingOrg | <p>code specifying the organisation who has created or owns the coding or numbering system</p> <ul style="list-style-type: none"> - base type: string, cod. table: NT6 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT6.xml (XPath GPDocRequest/refDoc/season/@numberingOrg) [Optional] (XPath GPDocRequest/itemRestrict/garmentPartCode/mod/@numberingOrg) [Optional] - nota: <i>this attribute should be ALTERNATIVE to the others</i> (XPath GPDocRequest/itemRestrict/acsCode/pattern/@numberingOrg) [Optional] - nota: <i>this attribute should be used either single or coupled with "listName" and "listVersion"</i> (XPath GPDocRequest/buyer/additionalIdentifier/@numberingOrg) [Optional] - nota: <i>here the issuer of the identifier must be specified</i> (XPath GPDocRequest/itemRestrict/texCode/pattern/@numberingOrg) [Optional] - nota: <i>this attribute should be used either single or coupled with "listName" and "listVersion"</i> (XPath GPDocRequest/itemRestrict/garmentPartCode/@numberingOrg) [Optional] (XPath GPDocRequest/itemRestrict/texCode/color/@numberingOrg) [Optional] - nota: <i>this attribute should be used either single or coupled with "listName" and "listVersion"</i> (XPath GPDocRequest/itemRestrict/garmentCode/@numberingOrg) [Optional] (XPath GPDocRequest/itemRestrict/texCode/added/@numberingOrg) [Optional] (XPath GPDocRequest/itemRestrict/yarnCode/color/@numberingOrg) [Optional] - nota: <i>this attribute should be used either single or coupled with "listName" and "listVersion"</i> (XPath GPDocRequest/itemRestrict/acsCode/added/@numberingOrg) [Optional] (XPath GPDocRequest/supplier/additionalIdentifier/@numberingOrg) [Optional] - nota: <i>here the issuer of the identifier must be specified</i> (XPath GPDocRequest/itemRestrict/note/@numberingOrg) [Optional] (XPath GPDocRequest/itemRestrict/acsCode/color/@numberingOrg) [Optional] - nota: <i>this attribute should be used either single or coupled with "listName" and "listVersion"</i> (XPath GPDocRequest/itemRestrict/yarnCode/added/@numberingOrg) [Optional] (XPath GPDocRequest/itemRestrict/yarnCode/@numberingOrg) [Optional] [Default=CL] (XPath GPDocRequest/itemRestrict/season/@numberingOrg) [Optional] (XPath GPDocRequest/supplier/id/@numberingOrg) [Optional] (XPath GPDocRequest/itemRestrict/id/@numberingOrg) [Optional] (XPath GPDocRequest/itemRestrict/yarnCode/art/@numberingOrg) [Optional] - nota: <i>this attribute should be used either single or coupled with "listName" and "listVersion"</i> (XPath GPDocRequest/refDoc/docID/@numberingOrg) [Optional] - nota: <i>here can be specified whose document numbering is used (e.g.: Client, Supplier, ..)</i> (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/added/@numberingOrg) [Optional] (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/color/@numberingOrg) [Optional] - nota: <i>this attribute should be used either single or coupled with "listName" and "listVersion"</i> (XPath GPDocRequest/itemRestrict/acsCode/@numberingOrg) [Optional] (XPath GPDocRequest/refDoc/attachment/fileName/@numberingOrg) [Optional] |

| | |
|----------|---|
| | <p>(XPath GPDocRequest/itemRestrict/acsCode/art/@numberingOrg) [Optional] - nota: <i>this attribute should be used either single or coupled with "listName" and "listVersion"</i></p> <p>(XPath GPDocRequest/itemRestrict/garmentPartCode/color/@numberingOrg) [Optional] - nota: <i>this attribute should be used either single or coupled with "listName" and "listVersion"</i></p> <p>(XPath GPDocRequest/note/@numberingOrg) [Optional] (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/garmentVariant/variantType/@numberingOrg) [Optional] - nota: <i>this attribute should be used either single or coupled with "listName" and "listVersion"</i></p> <p>(XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/garmentVariant/variantCode/@numberingOrg) [Optional] - nota: <i>this attribute should be used either single or coupled with "listName" and "listVersion"</i></p> <p>(XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/artGroup/@numberingOrg) [Optional] - nota: <i>this attribute should be used either single or coupled with "listName" and "listVersion"</i></p> <p>(XPath GPDocRequest/itemRestrict/garmentPartCode/added/@numberingOrg) [Optional] (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeA/art/@numberingOrg) [Optional] - nota: <i>this attribute should be used either single or coupled with "listName" and "listVersion"</i></p> <p>(XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/fabric/@numberingOrg) [Optional] - nota: <i>this attribute should be used either single or coupled with "listName" and "listVersion"</i></p> <p>(XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/@numberingOrg) [Optional] (XPath GPDocRequest/buyer/id/@numberingOrg) [Optional] (XPath GPDocRequest/itemRestrict/texCode/@numberingOrg) [Optional] (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/mod/@numberingOrg) [Optional] - nota: <i>this attribute should be ALTERNATIVE to the others</i></p> <p>(XPath GPDocRequest/itemRestrict/garmentPartCode/fabric/@numberingOrg) [Optional] - nota: <i>this attribute should be used either single or coupled with "listName" and "listVersion"</i></p> <p>(XPath GPDocRequest/itemRestrict/texCode/art/@numberingOrg) [Optional] - nota: <i>this attribute should be used either single or coupled with "listName" and "listVersion"</i></p> |
| pattern | <p>pattern/design number of the product, when not included in the article code - base type: string, max length: 15, (XPath GPDocRequest/itemRestrict/acsCode/pattern) 0-1 (XPath GPDocRequest/itemRestrict/texCode/pattern) 0-1</p> |
| person | <p>name of the contact person within a Party - base type: string, max length: 40, (XPath GPDocRequest/supplier/person) 0-1 (XPath GPDocRequest/buyer/person) 0-1</p> |
| @phone | <p>phone number of the contact person within a Party - base type: string, max length: 35, (XPath GPDocRequest/buyer/person/@phone) [Optional] (XPath GPDocRequest/supplier/person/@phone) [Optional]</p> |
| postCode | <p>code defining the postal zone - base type: string, max length: 10, (XPath GPDocRequest/supplier/postCode) 0-1 (XPath GPDocRequest/buyer/postCode) 0-1</p> |

| | |
|----------------|--|
| requestDocType | <p>type of document the issue of which is requested by the present Request message</p> <p>- base type: string, cod. table: T21 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T21.xml (XPath GPDocRequest/requestDocType) 1-1</p> |
| season | <p>sale season; defined as: season (1 crt) + year (4 crt) - season: S/S=1 A/W=2 Spring=3 Summer=4 Autumn=5 Winter=6: for more than four seasons use alphabetic sequence: 1st season=A 2nd season=B etc.etc.</p> <p>- base type: string, max length: 15, (XPath GPDocRequest/itemRestrict/season) 0-1 (XPath GPDocRequest/refDoc/season) 0-1</p> <p>- note: <i>here indicates the season to which the referenced document belongs</i></p> |
| @sender | <p>qualifier that specifies the Party issuing of the document</p> <p>- base type: boolean, (XPath GPDocRequest/supplier/@sender) [Optional]</p> <p>- nota: <i>This attribute is mandatory when the STYLESHEET must be used</i> (XPath GPDocRequest/buyer/@sender) [Optional]</p> <p>- nota: <i>This attribute is mandatory when the STYLESHEET must be used</i></p> |
| size | <p>size number of a fashion product (knitwear, clothing, ..)</p> <p>- base type: string, max length: 15, (XPath GPDocRequest/itemRestrict/garmentPartCode/size) 0-1 (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/size) 0-1</p> |
| street | <p>street and building number identifying a location</p> <p>- base type: string, max length: 80, (XPath GPDocRequest/buyer/street) 0-1 (XPath GPDocRequest/supplier/street) 0-1</p> |
| subCountry | <p>short name or code of the sub-country entity</p> <p>- base type: string, max length: 9, (XPath GPDocRequest/buyer/subCountry) 0-1 (XPath GPDocRequest/supplier/subCountry) 0-1</p> |
| subDept | <p>name or code of a contact department within a Party</p> <p>- base type: string, max length: 40, (XPath GPDocRequest/supplier/subDept) 0-1 (XPath GPDocRequest/buyer/subDept) 0-1</p> |
| @uid | <p>unique element identifier within the xml document</p> <p>- base type: string, (XPath GPDocRequest/refDoc/attachment/@uid) [Optional]</p> |
| uri | <p>Uniform Resource Identifier (URI) that identifies the external object as an Internet resource</p> <p>- base type: normalizedString, (XPath GPDocRequest/refDoc/attachment/externalReference/uri) 1-1</p> |
| @useProfile | <p>use profile to which the present document is compliant if it was agreed by the parties. It is suggested a URI with reference to the firms or the URL of the profile.</p> <p>- base type: string, (XPath GPDocRequest/@useProfile) [Optional]</p> |
| validityEnd | <p>date by which the validity ends, according to one of the patterns YYYY-MM-DD, YYYY-MM-DD:HH-MM or YYYY-WW.</p> <p>- base type: string, (XPath GPDocRequest/timeRestrict/validityEnd) 0-1</p> |
| validityStart | <p>date by which the validity starts, according to one of the patterns YYYY-MM-DD, YYYY-MM-DD:HH-MM or YYYY-WW.</p> <p>- base type: string, (XPath GPDocRequest/timeRestrict/validityStart) 0-1</p> |

| | |
|-------------|---|
| variantCode | Code of variant used for fashion product. - base type: string, (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/ garmentVariant/variantCode) 1-1 |
| variantType | Type of variant used for fashion product (examples: 'treatment', 'washing type', 'size class',...) - base type: string, (XPath GPDocRequest/itemRestrict/garmentCode/garmentCodeB/ garmentVariant/variantType) 1-1 |
| @version | Dictionary version from which the instance has been created - base type: string, cod. table: NT100 http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT100.xml (XPath GPDocRequest/@version) [Optional] [Default= draft] |

2.3 Enumeration tables

List of enumeration tables used in the XML document. You can find the corresponding codes at:
<http://www.ebiz-tcf.eu/moda-ml/imple/moda-ml-draft.asp?lingua=en&pag=6>

NT100 - eBIZ TCFUpstream version

NT29 - format of a date

NT6 - coding system owner/issuer

T10 - ISO3166 - Country

T21 - type of document

T44 - additional code type

T48 - garment part type

ACKNOWLEDGEMENT



This action is part of the eBIZ-4.0 project, which has received funding from the European Union's COSME Programme (2014 - 2020).



DISCLAIMER

The content of this document represents the views of the authors only and is their sole responsibility; it cannot be considered to reflect the views of the European Commission and/or the Executive Agency for Small and Medium-sized Enterprises (EASME) or any other body of the European Union.

The European Commission and the Agency do not accept any responsibility for use that may be made of the information it contains.


Annex A

Representative images of the principal complex elements' structure.




itemRestrict

Item restriction: Item restriction to be applied on the document requested, expressed as an article code or a Party code




refDoc

reference document details: identification of a document and of an item thereof, to which the message makes reference



timeRestrict

Time restriction: time restriction to be applied on the document requested, expressed as a period of validity/application of the document requested



Annex B

NT100 - eBIZ TCFUpstream version

dictionary version

Agency name: eBIZ

tabella cod.: NT100

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT100.xml

| Code | Description | Adoption note | Date of insertion |
|--------|-------------|---------------|-------------------|
| 2013-1 | v2013-1 | | 01/07/2013 |
| 2018-1 | v2018-1 | | 04/11/2018 |
| draft | draft | | 08/09/2017 |

NT29 - format of a date

format used for the date

Agency name: eBIZ

tabella cod.: NT29

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT29.xml

| Code | Description | Adoption note | Date of insertion |
|------|------------------|---------------|-------------------|
| D | YYYY-MM-DD | | |
| M | YYYY-MM-DD:HH-MM | | |
| W | YYYY-WW | | |

NT6 - coding system owner/issuer

code specifying the organisation who has created or owns the coding or numbering system

Agency name: eBIZ

tabella cod.: NT6

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_NT6.xml

| Code | Description | Adoption note | Date of insertion |
|------|------------------------------|---------------|-------------------|
| CL | Customer/buyer | | |
| CO | Quality Controller | | |
| EN | GS1 (ex-EAN International) | | |

| | | | |
|----|------------------|--|------------|
| ES | e-Stockflow | | |
| FO | Supplier | | |
| GS | GS1 | | 01/07/2013 |
| MF | VAT identifier | | |
| ML | Moda-ML | | |
| SP | Service Provider | | |

T10 - ISO3166 - Country

code of the nation

Agency name: ISO

tabella cod.: T10

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T10.xml

Table not printed: there are 239 elements, more than the maximum specified for printing: 99.

T21 - type of document

type or class to which the referenced document belongs

Agency name: eBIZ

tabella cod.: T21

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T21.xml

| Code | Description | Adoption note | Date of insertion |
|------|------------------------------|---------------|-------------------|
| BOR | blanket order | | 01/02/2018 |
| CAT | Price catalogue - tech sheet | | |
| CEO | Certificate of origin | | 13/04/2018 |
| CER | Certificate | | 13/04/2018 |
| COC | colour card | | |
| CRN | Credit note | | 08/09/2017 |
| CTO | Checking order | | 01/07/2013 |
| CTR | Contract | | |
| CXF | CxF3 file | | 01/07/2013 |
| DAD | Darn order | | |
| DDT | ddt | | |
| DEA | Despatch advise | | |

| | | | |
|-----|---|--|------------|
| DER | Despatch request | | |
| DR | Document Request | | 02/12/2014 |
| FOR | Forecast | | 02/12/2014 |
| GSO | Garment stock offer | | |
| GSX | Garment stock offer change | | |
| INV | Invoice | | |
| KCC | Knitting-Clothing Commission Order | | 02/12/2014 |
| KCI | Garment in Work Inventory Report | | 02/12/2014 |
| M2M | Made to Measure Production Order | | 02/12/2014 |
| MAS | Master marker | | |
| MCI | Visual merchandising instruction | | 13/04/2018 |
| OCH | Order change | | |
| OFF | Offer | | |
| ORD | Purchase order | | |
| ORP | Order response | | |
| OSR | order status request | | |
| OSS | Offer status | | 02/12/2014 |
| OST | Order status | | |
| OUR | our reference | | |
| QR | Quality Report | | 02/12/2014 |
| RAI | Raw Material in Work Inventory Report | | 02/12/2014 |
| RDC | Raw dyeing commission order | | |
| RDH | Raw dyeing order change | | |
| RDR | Raw dyeing order response | | |
| REA | Receiving advise | | |
| REQ | Request for Offer | | |
| RET | Return | | 02/12/2014 |
| RSC | Spinning commission order | | |
| RSH | Spinning order change | | |
| RSR | Spinning order response | | |
| SCL | process sheet | | |
| TFC | Textile dyeing-finishing commission order | | |
| TFX | Textile Dyeing-Finishing Order Change | | 02/12/2014 |
| TPC | Textile printing commission order | | |
| TPX | Textile Printing Order Change | | 02/12/2014 |

| | | | |
|-----|-----------------------------------|--|------------|
| TWI | Textile in work inventory | | |
| VMI | visual merchandising instructions | | 01/02/2018 |
| WAC | Warping commission order | | |
| WEC | Weaving commission order | | |
| YDC | Yarn dyeing commission order | | |
| YDH | Yarn dyeing order change | | |
| YDR | Yarn dyeing order response | | |
| YTC | Twisting commission order | | |
| YWI | Yarn in work inventory | | |

T44 - additional code type

qualifier of the additional coding of a product

Agency name: eBIZ

tabella cod.: T44

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T44.xml

| Code | Description | Adoption note | Date of insertion |
|------|-----------------------------|---------------|-------------------|
| CC | colour card | | |
| CL | sales collection | | |
| CO | company identification code | | 08/09/2017 |
| DY | dye number | | |
| LT | lot number | | |
| MDI | Made in | | 08/09/2017 |
| MS | manufacturing state | | |
| PKG | packaging | | 09/09/2014 |
| PL | product line | | |
| RGB | RGB value | | |
| SE | selvedge code | | |

T48 - garment part type

code specifying the type of component or part of a garment (sleeve, neck, ...)

Agency name: eBIZ

tabella cod.: T48

File codes list (Generic code): http://www.ebiz.enea.it/moda-ml/repository/codelist/draft/gc_T48.xml

| Code | Description | Adoption note | Date of insertion |
|-------------|--------------------|----------------------|--------------------------|
| BB | bottom back | | 01/08/2018 |
| BF | bottom fore/front | | 01/08/2018 |
| CO | collar | | 01/08/2018 |
| CU | cuff | | 01/08/2018 |
| DV | fore | | |
| EM | embroidery | | 01/08/2018 |
| OC | other component | | 01/08/2018 |
| PO | pocket | | 01/08/2018 |
| SC | back | | |
| SL | sleeve | | 01/08/2018 |
| TB | top back | | 01/08/2018 |
| TF | top fore/front | | 01/08/2018 |